

PROBLEM SUMMARY

KAESER AIRCENTER SK 20 6533823 (S/N 1227)

Compressor



KAESER SIGMA (OEM) M-460 (--- GAL)

COMPONENT CONDITION SUMMARY



RECOMMENDATION

No corrective action is recommended at this time. Resample at the next service interval to monitor.

PROBLEMATIC TEST RESULTS										
Sample Status				ABNORMAL	ATTENTION	ABNORMAL				
Visc @ 40°C	cSt	ASTM D445	45	<u> </u>	48.6	53.1				

Customer Id: BUZMIL Sample No.: KCP49951 Lab Number: 05664112 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Jonathan Hester +1 919-379-4092 x4092 jhester@wearcheckusa.com

To change component or sample information: Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u>

RECOMMENDED ACTIONS

There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS

21 Mar 2022 Diag: Don Baldridge



The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.All component wear rates are normal. There is a moderate amount of particulates present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



12 Jul 2021 Diag: Doug Bogart



Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.All component wear rates are normal. There is a high amount of particulates present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



08 Apr 2021 Diag: Angela Borella

NORMAL



Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.All component wear rates are normal. There is no indication of any contamination in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.







OIL ANALYSIS REPORT

Machine Id KAESER AIRCENTER SK 20 6533823 (S/N 1227) Component

Compressor Fluid

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The oil viscosity is higher than normal. The AN level is acceptable for this fluid.



SAMPLE INFURI		method	limit/base	current	nistory i	nistory2
Sample Number		Client Info		KCP49951	KCP45291	KCP42344
Sample Date		Client Info		06 Oct 2022	21 Mar 2022	12 Jul 2021
Machine Age	hrs	Client Info		24107	20732	16487
Oil Age	hrs	Client Info		3000	2000	2300
Oil Changed		Client Info		Not Changd	Not Changd	Changed
Sample Status				ABNORMAL	ATTENTION	ABNORMAL
		mothod	limit/booo	ourropt	biotoput	history?
WEAR METALS		methou	IIIIIVDase	Current	HIStory	TIIStOLY2
Iron	ppm	ASTM D5185m	>50	0	0	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	<1	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>10	0	<1	0
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	23	2	9
lin	ppm	ASTM D5185m	>10	0	0	<1
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	<1
Barium	ppm	ASTM D5185m	90	2	72	<1
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	100	<1	87	24
Calcium	ppm	ASTM D5185m	0	<1	1	<1
Phosphorus	ppm	ASTM D5185m	0	8	3	<1
Zinc	ppm	ASTM D5185m	0	<1	<1	12
Sulfur	ppm	ASTM D5185m	23500	24025	18384	18809
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	maa	ASTM D5185m	>25	2	<1	0
Sodium	mag	ASTM D5185m	- 10	0	5	7
Potassium	maa	ASTM D5185m	>20	<1	0	<1
Water	%	ASTM D6304	>0.05	0.008	0.021	0.025
ppm Water	ppm	ASTM D6304	>500	87.4	218.2	257.5
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		5406	9403	18687
Particles >6µm		ASTM D7647	>1300	641	A 2156	▲ 5468
Particles >14µm		ASTM D7647	>80	20	1 38	3 78
Particles >21µm		ASTM D7647	>20	6	<u> </u>	1 25
Particles >38µm		ASTM D7647	>4	0	2	 7
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	20/17/11	▲ 18/14	▲ 20/16
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.47	0.44	0.393

Report Id: BUZMIL [WUSCAR] 05664112 (Generated: 08/08/2023 08:52:31) Rev: 1

Contact/Location: MATHEW STORK - BUZMIL



Acid Number

1.20

OIL ANALYSIS REPORT









Bottom



Contact/Location: MATHEW STORK - BUZMIL