


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id KAESER AS 25T 6697489 (S/N 1250)

Compressor

KAESER SIGMA (OEM) S-460 (--- QTS)

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| | Aug ² 019 | | 2010 | Sep [‡] 021 Sep [‡] 002 | | |
|-----------------|----------------------|---------------|------------|---|--------------|----------------|
| SAMPLE INFORM | ATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | KCP46985D | KC05384264 | KC79483 |
| Sample Date | | Client Info | | 28 Sep 2022 | 09 Sep 2021 | 14 Aug 2019 |
| Machine Age | hrs | Client Info | | 19068 | 12893 | 2269 |
| Oil Age | hrs | Client Info | | 2937 | 0 | 0 |
| Oil Changed | 1113 | Client Info | | Changed | Not Changd | Changed |
| Sample Status | | Oliciti IIIIo | | NORMAL | ABNORMAL | ABNORMAL |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 0 | <1 | <1 |
| Chromium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Nickel | ppm | ASTM D5185m | >3 | 0 | 0 | <1 |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185m | >2 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | | <1 | <1 | <1 |
| Lead | ppm | ASTM D5185m | >10 | 2 | <1 | 2 |
| | | ASTM D5185m | | 6 | 9 | 3 |
| Copper Tin | ppm | ASTM D5185m | >10 | 0 | 0 | 0 |
| | ppm | | >10 | | <1 | 0 |
| Antimony | ppm | ASTM D5185m | | | | 2 |
| Vanadium | ppm | ASTM D5185m | | <1 0 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | | - | 0 | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Barium | ppm | ASTM D5185m | 90 | 27 | 13 | 38 |
| Molybdenum | ppm | ASTM D5185m | | 0 | 0 | <1 |
| Manganese | ppm | ASTM D5185m | | <1 | 0 | <1 |
| Magnesium | ppm | ASTM D5185m | 90 | 66 | 51 | 74 |
| Calcium | ppm | ASTM D5185m | 2 | 0 | 0 | 4 |
| Phosphorus | ppm | ASTM D5185m | | 17 | 5 | 2 |
| Zinc | ppm | ASTM D5185m | | 8 | 11 | 9 |
| Sulfur | ppm | ASTM D5185m | | 22908 | 16230 | 17219 |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | 1 | <1 | 1 |
| Sodium | ppm | ASTM D5185m | | 50 | 15 | 28 |
| Potassium | ppm | ASTM D5185m | >20 | 8 | <1 | 28 |
| Water | % | ASTM D6304 | >0.05 | 0.017 | 0.025 | 0.032 |
| ppm Water | ppm | ASTM D6304 | >500 | 170.6 | 257.5 | 328.0 |
| FLUID CLEANLINE | ESS | method | limit/base | current | history1 | history2 |
| Particles >4μm | | ASTM D7647 | | 3138 | 10924 | 9125 |
| Particles >6μm | | ASTM D7647 | >1300 | 562 | ▲ 3581 | ▲ 3765 |
| Particles >14μm | | ASTM D7647 | >80 | 31 | ▲ 462 | ▲ 386 |
| Particles >21μm | | ASTM D7647 | >20 | 8 | <u>▲</u> 143 | <u> 111</u> |
| Particles >38µm | | ASTM D7647 | >4 | 0 | <u> 7</u> | <u> </u> |
| Particles >71μm | | ASTM D7647 | >3 | 0 | 0 | 1 |
| Oil Cleanliness | | ISO 4406 (c) | >/17/13 | 19/16/12 | <u>19/16</u> | △ 19/16 |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| | | | | | | |

0.348

0.383



OIL ANALYSIS REPORT

