


# **OIL ANALYSIS REPORT**

## **Sample Rating Trend**



NORMAL



# Machine Id A101 Component Hydraulic System

**MOBIL DTE 10 EXCEL 32 (43 GAL)** 

וט	ΙΔ		VП			15
	$\neg$	uі		$\smile$	J	ı

## Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

There is no indication of any contamination in the component. The amount and size of particulates present in the system is acceptable.

## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Mar2011 O	ct2014 Sep2015 Sep	2016 Feb2018 Oct2019	Oct2021	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		MHI017498	MHI017695	MHI018592
Sample Date		Client Info		26 Oct 2022	26 Oct 2021	15 Oct 2020
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		79898	74571	78187
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	3	0	1
Chromium	ppm	ASTM D5185m		<1	0	0
Nickel	ppm	ASTM D5185m		3	<1	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m		<1	0	0
Lead	ppm	ASTM D5185m		<1	0	<1
Copper	ppm	ASTM D5185m		<1	0	<1
Tin	ppm	ASTM D5185m		0	0	0
Antimony	ppm	ASTM D5185m			0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<1	0	1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m		0	0	<1
Calcium	ppm	ASTM D5185m	120	111	102	102
Phosphorus	ppm	ASTM D5185m	475	444	409	402
Zinc	ppm	ASTM D5185m		15	29	32
Sulfur	ppm	ASTM D5185m	1275	1885	1332	1438
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>+30	<1	0	0
Sodium	ppm	ASTM D5185m		2	1	0
Potassium	ppm	ASTM D5185m	>20	0	0	0
Water	%	ASTM D6304	>0.1	0.007	0.003	0.003
ppm Water	ppm	ASTM D6304	>1000	71.6	33.7	37.2
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	1207	963	242
Particles >6µm		ASTM D7647	>1300	368	227	73
Particles >14µm		ASTM D7647	>160	51	20	6
Particles >21µm		ASTM D7647	>40	12	4	1
Particles >38µm		ASTM D7647	>10	0	0	0
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	17/16/13	17/15/11	15/13/10
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2



## **OIL ANALYSIS REPORT**

