


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



KAESER 7312838

Component

Compressor

KAESER SIGMA (OEM) S-460 (--- QTS)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Mar2022	Nov2022		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCP47015	KCP44153	
Sample Date		Client Info		16 Nov 2022	17 Mar 2022	
Machine Age	hrs	Client Info		7561	5782	
Oil Age	hrs	Client Info		1779	5782	
Oil Changed	1110	Client Info		Not Changd	Changed	
Sample Status				NORMAL	ATTENTION	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	<1	0	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	0	<1	
Aluminum	ppm	ASTM D5185m	>10	<1	<1	
Lead	ppm	ASTM D5185m	>10	<1	0	
Copper	ppm	ASTM D5185m	>50	2	6	
Tin	ppm	ASTM D5185m	>10	<1	<1	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m	90	26	6	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		0	<1	
Magnesium	ppm	ASTM D5185m	90	77	49	
Calcium	ppm	ASTM D5185m	2	2	1	
Phosphorus	ppm	ASTM D5185m		9	3	
Zinc	ppm	ASTM D5185m		2	8	
Sulfur	ppm	ASTM D5185m		22076	16389	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	1	<1	
Sodium	ppm	ASTM D5185m		21	15	
Potassium	ppm	ASTM D5185m		8	7	
Water	%	ASTM D6304	>0.05	0.021	0.017	
ppm Water	ppm	ASTM D6304	>500	216.0	176.7	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		4223	7051	
Particles >6µm		ASTM D7647	>1300	801	▲ 2010	
Particles >14μm		ASTM D7647	>80	37	74	
Particles >21µm		ASTM D7647	>20	9	13	
Particles >38μm		ASTM D7647	>4	0	2	
Particles >71μm		ASTM D7647	>3	0	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	19/17/12	1 8/13	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
A aid Niumbar (ANI)	ma 1/011/-	ACTM DOGAE	0.4	0.22	0.22	

Acid Number (AN)

mg KOH/g ASTM D8045 0.4

0.33

0.33



OIL ANALYSIS REPORT

