

## **OIL ANALYSIS REPORT**

3201-B - 3200-B CRYSTALL Component

Gearbox Fluic

Area **P1** 

### MOBIL MOBILGEAR 600 XP ISO 150 (27 QTS

#### Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is a light amount of silt (particulates < 14 microns in size) present in the oil. The water content is negligible.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

LIZER						
S)		Jan2020	Feb2021 Aug2021	Feb2022 May2022 Aug2022	Dec2022	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0752478	WC0723561	WC0670731
Sample Date		Client Info		01 Dec 2022	08 Aug 2022	05 May 2022
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				ATTENTION	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	6	5	6
Chromium	ppm	ASTM D5185m		0	0	0
Nickel	ppm	ASTM D5185m	>15	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	<1	<1
Aluminum	ppm	ASTM D5185m		0	0	0
_ead	ppm	ASTM D5185m	>100	0	0	0
Copper	ppm	ASTM D5185m	>200	<1	0	0
Tin	ppm	ASTM D5185m	>25	0	<1	0
Antimony	ppm	ASTM D5185m	>5			
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		10	15	17
Barium	ppm	ASTM D5185m		<1	0	0
Volybdenum	ppm	ASTM D5185m		0	0	0
Vanganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		<1	0	0
Calcium	ppm	ASTM D5185m		3	0	1
Phosphorus	ppm	ASTM D5185m		340	312	307
Zinc	ppm	ASTM D5185m		8	3	0
Sulfur	ppm	ASTM D5185m		13942	12097	10369
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	<1	0	<1
Sodium	ppm	ASTM D5185m		1	0	0
Potassium	ppm	ASTM D5185m	>20	0	0	2
Water	%	ASTM D6304		0.017	0.010	0.006
opm Water	ppm	ASTM D6304	>2000	179.6	106.6	63.7
FLUID CLEANLIN	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	<b>37969</b>	67754	▲ 72429
Particles >6µm		ASTM D7647		1540	2453	2438
Particles >14µm		ASTM D7647	>640	40	94	96
Particles >21µm		ASTM D7647		7	17	22
Particles >38µm		ASTM D7647	>40	0	1	0
Particles >71µm		ASTM D7647		0	0	0
Oil Cleanliness		ISO 4406 (c)	>21/19/16	<b>22/18/12</b>	<u> </u>	<b>2</b> 3/18/14
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2

Acid Number (AN)

mg KOH/g ASTM D8045

0.80 0.76

Submitted By: BRENT FORSYTHE

0.80


ISO


Report Id: AJIRAL [WUSCAR] 05710371 (Generated: 01/26/2024 09:21:06) Rev: 1


Sample Rating Trend



# **OIL ANALYSIS REPORT**








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	TIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	150	149	148	148
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color						

Bottom



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Submitted By: BRENT FORSYTHE

Page 2 of 2

F: