

# **OIL ANALYSIS REPORT**

# Sample Rating Trend



KAESER 7352439 Component

#### Compressor Fluid

KAESER SIGMA (OEM) M-460 (--- GAL)

## DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

## Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMI LE INI ONI		пешоа	iiiiii/base	current	nistory i	THSTOLA
Sample Number		Client Info		KCP49863	KCP40190	KCP41025
Sample Date		Client Info		05 Dec 2022	30 Jun 2022	14 Mar 2022
Machine Age	hrs	Client Info		4337	4017	3820
Oil Age	hrs	Client Info		800	300	800
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Sample Status				NORMAL	ABNORMAL	ABNORMAL
		ام مالح میں	1:00:14/10:00:00		Intertermed	laistem (O
WEAR METALS		methoa	iinii/base	current	riistory i	nistory2
Iron	ppm	ASTM D5185m	>50	0	<1	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	<1	<1	<1
Lead	ppm	ASTM D5185m	>10	<1	<1	0
Copper	ppm	ASTM D5185m	>50	1	3	1
Tin	ppm	ASTM D5185m	>10	<1	0	<1
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	<1
Barium	ppm	ASTM D5185m	90	52	50	59
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	100	87	79	74
Calcium	ppm	ASTM D5185m	0	2	2	0
Phosphorus	ppm	ASTM D5185m	0	8	0	0
Zinc	ppm	ASTM D5185m	0	4	4	0
Sulfur	ppm	ASTM D5185m	23500	23632	22795	15317
CONTAMINANTS	\$	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	1	<1	0
Sodium	ppm	ASTM D5185m		9	15	5
Potassium	ppm	ASTM D5185m	>20	9	7	<1
Water	%	ASTM D6304	>0.05	0.017	0.031	0.014
ppm Water	ppm	ASTM D6304	>500	177.6	316.8	142.2
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		2222	21819	10459
Particles >6µm		ASTM D7647	>1300	795	▲ 6969	<b>A</b> 2891
Particles >14µm		ASTM D7647	>80	36	▲ 562	162
Particles >21µm		ASTM D7647	>20	5	<u> </u>	16
Particles >38µm		ASTM D7647	>4	0	3	1
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	18/17/12	▲ 22/20/16	▲ 19/15
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.37	0.35	0.37

Report Id: AMAKER [WUSCAR] 05715896 (Generated: 11/14/2023 08:57:25) Rev: 1

Contact/Location: B. LANCRON - AMAKER



**OIL ANALYSIS REPORT** 







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	45	48.3	51.5	46.9
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color						
_						

Bottom



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: B. LANCRON - AMAKER

F: