


# **OIL ANALYSIS REPORT**



**NORMAL** 



8291218 (S/N 1031)

Component

**Compressor** Fluid

KAESER SIGMA (OEM) M-460 (--- GAL)

	$\sim$		$\overline{}$	
 ΙД	( en	VИ	วร	15
 $I \cap$	ч	N.	-	-

## Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sample Number         Client Info         KCP49866             Sample Date         Client Info         14 Dec 2022             Machine Age         hrs         Client Info         2631             Oil Age         hrs         Client Info         2000             Oil Changed         Client Info         Changed             Sample Status         NORMAL             WEAR METALS         method         limit/base         current         history1         his           Iron         ppm         ASTM D5185m         >50         <1             Chromium         ppm         ASTM D5185m         >10         <1             Nickel         ppm         ASTM D5185m         >3         <1	story2
Sample Number         Client Info         KCP49866             Sample Date         Client Info         14 Dec 2022             Machine Age         hrs         Client Info         2631             Oil Age         hrs         Client Info         2000             Oil Changed         Client Info         Changed             Sample Status         NORMAL             WEAR METALS         method         limit/base         current         history1         his           Iron         ppm         ASTM D5185m         >50         <1             Chromium         ppm         ASTM D5185m         >10         <1             Nickel         ppm         ASTM D5185m         >3         <1	
Sample Date         Client Info         14 Dec 2022             Machine Age         hrs         Client Info         2631             Oil Age         hrs         Client Info         2000             Oil Changed         Client Info         Changed             Sample Status         NORMAL             WEAR METALS         method         limit/base         current         history1         his           Iron         ppm         ASTM D5185m         >50         <1             Chromium         ppm         ASTM D5185m         >10         <1             Nickel         ppm         ASTM D5185m         >3         <1	story2
Machine Age         hrs         Client Info         2631             Oil Age         hrs         Client Info         2000             Oil Changed         Client Info         Changed             Sample Status         NORMAL             WEAR METALS         method         limit/base         current         history1         his           Iron         ppm         ASTM D5185m         >50         <1             Chromium         ppm         ASTM D5185m         >10         <1             Nickel         ppm         ASTM D5185m         >3         <1	story2
Oil Age         hrs         Client Info         2000             Oil Changed         Client Info         Changed             Sample Status         NORMAL             WEAR METALS         method         limit/base         current         history1         his           Iron         ppm         ASTM D5185m         >50         <1             Chromium         ppm         ASTM D5185m         >10         <1             Nickel         ppm         ASTM D5185m         >3         <1	story2
Oil Changed         Client Info         Changed             Sample Status         NORMAL             WEAR METALS         method         limit/base         current         history1         his           Iron         ppm         ASTM D5185m         >50         <1             Chromium         ppm         ASTM D5185m         >10         <1             Nickel         ppm         ASTM D5185m         >3         <1	story2
Sample Status         NORMAL             WEAR METALS         method         limit/base         current         history1         his           Iron         ppm         ASTM D5185m         >50         <1             Chromium         ppm         ASTM D5185m         >10         <1             Nickel         ppm         ASTM D5185m         >3         <1	story2
WEAR METALS         method         limit/base         current         history1         his           Iron         ppm         ASTM D5185m         >50         <1             Chromium         ppm         ASTM D5185m         >10         <1             Nickel         ppm         ASTM D5185m         >3         <1	story2
Iron         ppm         ASTM D5185m         >50         <1	story2
Chromium         ppm         ASTM D5185m         >10         <1	
Nickel ppm ASTM D5185m >3 <1	
TI. 1	
Titanium         ppm         ASTM D5185m         >3         0	
Silver ppm ASTM D5185m >2 <1	
Aluminum         ppm         ASTM D5185m         >10         <1	
Lead         ppm         ASTM D5185m         >10         1	
Copper         ppm         ASTM D5185m         >50         5	
Tin ppm ASTM D5185m >10 <1	
Vanadium ppm ASTM D5185m <1	
Cadmium         ppm         ASTM D5185m         0	
ADDITIVES method limit/base current history1 his	story2
<b>Boron</b> ppm ASTM D5185m 0 <b>0</b>	
Barium         ppm         ASTM D5185m         90         0	
Molybdenum         ppm         ASTM D5185m         0         <1	
ManganeseppmASTM D5185m0	
Magnesium         ppm         ASTM D5185m         100         7	
Calcium         ppm         ASTM D5185m         0         0	
Phosphorus ppm ASTM D5185m 0 21	
<b>Zinc</b> ppm ASTM D5185m 0 <b>0</b>	
Sulfur         ppm         ASTM D5185m         23500         9487	
CONTAMINANTS method limit/base current history1 his	story2
Silicon ppm ASTM D5185m >25 <1	
Sodium         ppm         ASTM D5185m         4	
Potassium ppm ASTM D5185m >20 <b>14</b>	
Water % ASTM D6304 >0.05 <b>0.017</b>	
ppm Water	
FLUID CLEANLINESS method limit/base current history1 his	story2
Particles >4μm ASTM D7647 <b>327</b>	
Particles >6μm ASTM D7647 >1300 <b>101</b>	
Particles >14μm ASTM D7647 >80 <b>15</b>	
Particles >21μm ASTM D7647 >20 <b>5</b>	
Particles >38μm ASTM D7647 >4 <b>0</b>	
Particles >71 $\mu$ m ASTM D7647 >3 <b>0</b>	
Oil Cleanliness ISO 4406 (c) >/17/13 <b>16/14/11</b>	
FLUID DEGRADATION method limit/base current history1 his	story2

Acid Number (AN)

mg KOH/g ASTM D8045 1.0

0.39



# **OIL ANALYSIS REPORT**

