


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id KAESER SFC 45S 5507867 (S/N 1024)

Compressor

KAESER SIGMA (OEM) FG-460 (--- GAL)

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Mar2018	lov2018 Aug2019 Jan20	120 May2021 Dec2021 May202	2 Dec2022	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCP55503	KCP50379	KCP36914
Sample Date		Client Info		09 Dec 2022	16 May 2022	30 Dec 2021
Machine Age	hrs	Client Info		40090	36770	34830
Oil Age	hrs	Client Info		5500	2100	3069
Oil Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	ABNORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	2	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	3	<u>^</u> 24	3
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m		<1	<1	<1
Tin	ppm	ASTM D5185m	>10	0	0	0
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	<1
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m		<1	0	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m	500	50	362	109
Zinc	ppm	ASTM D5185m		35	256	117
Sulfur	ppm	ASTM D5185m		1681	1477	1109
CONTAMINANTS	5	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	0
Sodium	ppm	ASTM D5185m		0	2	<1
Potassium	ppm	ASTM D5185m	>20	0	0	0
Water	%	ASTM D6304	>0.05	0.007	0.006	0.003
ppm Water	ppm	ASTM D6304	>500	77.3	66.4	26.1
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		5280	2788	5323
Particles >6µm		ASTM D7647	>1300	425	535	434
Particles >14µm		ASTM D7647	>80	16	58	28
Particles >21µm		ASTM D7647	>20	5	13	12
Particles >38µm		ASTM D7647	>4	1	1	1
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	20/16/11	19/16/13	16/12
FLUID DEGRADA	NOITA	method	limit/base	current	history1	history2
	1/011/	10TH D0045		0.40		

Acid Number (AN)

mg KOH/g ASTM D8045 1.5

1.04

0.55

Report Id: TULBAL [WUSCAR] 05734169 (Generated: 02/20/2024 06:10:20) Rev: 1

Contact/Location: S. SMITH - TULBAL



OIL ANALYSIS REPORT

