


# **OIL ANALYSIS REPORT**

## Sample Rating Trend







# Machine Id C107 Component Hydraulic System Fluid

**MOBIL DTE 10 EXCEL 32 (43 GAL)** 

D	ΙΛ				124	
	II —	CI.	BY N	U	J	ı

## Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jun2011	Jan2015 Dec2016	Mar2018 Dec2019 D	ec2021	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		MHI025217	MHI017479	MHI017444
Sample Date		Client Info		15 Dec 2022	21 Dec 2021	30 Nov 2020
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		87633	81785	75470
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	9	7	5
Chromium	ppm	ASTM D5185m	>20	0	0	0
Nickel	ppm	ASTM D5185m	>20	4	3	1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m	>20	0	0	0
Lead	ppm	ASTM D5185m	>20	<1	1	1
Copper	ppm	ASTM D5185m	>20	<1	<1	<1
Tin	ppm	ASTM D5185m	>20	0	0	0
Antimony	ppm	ASTM D5185m			0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	2	<1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	100	0	0	<1
Calcium	ppm	ASTM D5185m	120	111	120	115
Phosphorus	ppm	ASTM D5185m	475	440	494 22	444 21
Zinc	ppm	ASTM D5185m	1075	30 1740	1472	
Sulfur	ppm	ASTM D5185m	1275	1740	1472	1338
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>+30	<1	<1	0
Sodium	ppm	ASTM D5185m		2	2	2
Potassium	ppm	ASTM D5185m	>20	0	0	0
Water	%	ASTM D6304	>0.1	0.011	0.002	0.004
ppm Water	ppm	ASTM D6304	>1000	112.0	19.6	44.1
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	1545	253	585
Particles >6µm		ASTM D7647	>1300	308	71	186
Particles >14µm		ASTM D7647	>160	41	22	26
Particles >21µm		ASTM D7647		15	12	11
Particles >38µm		ASTM D7647	>10	1	0	0
Particles >71μm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	18/15/13	15/13/12	16/15/12
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

Acid Number (AN)

mg KOH/g ASTM D8045

**0.12** 0.171 0.055

Contact/Location: DANIEL BOYD - DIADIL



# **OIL ANALYSIS REPORT**

