




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Machine Id  
**MACK TRACTOR 56**  
 Component  
**Diesel Engine**  
 Fluid  
**DIESEL ENGINE OIL SAE 15W40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>WC0721153</b>	WCDB3651	WCDB1126
Sample Date	Client Info		<b>13 Dec 2022</b>	17 Oct 2019	21 Jun 2018
Machine Age	hrs	Client Info	<b>25557</b>	25125	24857
Oil Age	hrs	Client Info	<b>500</b>	500	500
Oil Changed	Client Info		<b>Changed</b>	Changed	Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method		<b>NEG</b>	NEG	NEG

## WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >120	<b>18</b>	12	24
Chromium	ppm	ASTM D5185m >20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m >5	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185m >2	<b>&lt;1</b>	<1	0
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	0
Aluminum	ppm	ASTM D5185m >20	<b>0</b>	2	2
Lead	ppm	ASTM D5185m >40	<b>2</b>	4	1
Copper	ppm	ASTM D5185m >330	<b>2</b>	1	2
Tin	ppm	ASTM D5185m >15	<b>1</b>	0	<1
Antimony	ppm	ASTM D5185m	<b>---</b>	2	0
Vanadium	ppm	ASTM D5185m	<b>0</b>	0	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 250	<b>11</b>	18	37
Barium	ppm	ASTM D5185m 10	<b>12</b>	0	0
Molybdenum	ppm	ASTM D5185m 100	<b>63</b>	64	68
Manganese	ppm	ASTM D5185m	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 450	<b>823</b>	957	905
Calcium	ppm	ASTM D5185m 3000	<b>1078</b>	1111	1126
Phosphorus	ppm	ASTM D5185m 1150	<b>957</b>	1017	932
Zinc	ppm	ASTM D5185m 1350	<b>1149</b>	1142	1112
Sulfur	ppm	ASTM D5185m 4250	<b>3110</b>	2720	2973

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	<b>4</b>	4	6
Sodium	ppm	ASTM D5185m >158	<b>2</b>	2	4
Potassium	ppm	ASTM D5185m >20	<b>0</b>	<1	1

## INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >4	<b>0.3</b>	0.3	0.3
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.8</b>	7.7	8.
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>18.4</b>	18	17.

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>14.7</b>	14	13.
Base Number (BN)	mg KOH/g	ASTM D2896 8.5	<b>9.55</b>	9.73	7.96











# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	<b>13.5</b>	13.6	12.91

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0721153 **Received** : 23 Jan 2023  
**Lab Number** : **05747278** **Diagnosed** : 24 Jan 2023  
**Unique Number** : 10306882 **Diagnostician** : Wes Davis  
**Test Package** : MOB 2

**TRESCA BROS SAND & GRAVEL INC**  
 66 MAIN ST  
 MILLIS, MA  
 US 02054  
 Contact: FRAN ROSSI  
 frossi@trescaconcrete.com  
 T: (508)376-2957  
 F: (508)376-4333

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)