


# **OIL ANALYSIS REPORT**







# **DRYERS A-681**

Component Gearbox

MOBIL SHC 630 (1 LTR)

### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The water content is negligible. The system and fluid cleanliness is acceptable.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jan 2020	Sep2020 Apr2021	Oct2021 May2022 Sep2022	Feb2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0788651	WC0739591	WC0699954
Sample Date		Client Info		09 Feb 2023	14 Sep 2022	09 May 2022
Machine Age	yrs	Client Info		9	8	8
Oil Age	yrs	Client Info		1	0	0
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	3	2	6
Chromium	ppm	ASTM D5185m	>15	0	0	0
Nickel	ppm	ASTM D5185m	>15	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	<1	<1
Aluminum	ppm	ASTM D5185m	>25	0	0	<1
Lead	ppm	ASTM D5185m	>100	0	0	<1
Copper	ppm	ASTM D5185m	>200	0	0	0
Tin	ppm	ASTM D5185m	>25	0	<1	<1
Antimony	ppm	ASTM D5185m	>5			
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m		<1	0	0
Calcium	ppm	ASTM D5185m		1	0	5
Phosphorus	ppm	ASTM D5185m		436	473	491
Zinc	ppm	ASTM D5185m		0	<1	0
Sulfur	ppm	ASTM D5185m		112	0	33
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	50	44	<b>△</b> 66
Sodium	ppm	ASTM D5185m		0	0	0
Potassium	ppm	ASTM D5185m	>20	<1	0	0
Water	%	ASTM D6304	>0.2	0.006	0.004	0.028
ppm Water	ppm	ASTM D6304	>2000	62.0	46.0	288.7
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	7365		
Particles >6µm		ASTM D7647	>5000	2240		
Particles >14µm		ASTM D7647	>640	196		
Particles >21µm		ASTM D7647	>160	41		
Particles >38µm		ASTM D7647	>40	5		
Particles >71µm		ASTM D7647	>10	1		
Oil Cleanliness		ISO 4406 (c)	>21/19/16	20/18/15		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

0.48



## **OIL ANALYSIS REPORT**





Lab Number **Unique Number** 

: 05768050 : 10337658

Diagnosed : 16 Feb 2023 Diagnostician

: Wes Davis Test Package : IND 2 ( Additional Tests: KF, PrtCount )

Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

GROTON, SD

US 57445-6400 Contact: GAVIN KRUEGER Gavin.Krueger@POET.COM T: 6(05)846-6863

F: (605)397-2754