

OIL ANALYSIS REPORT

7319181 (S/N 1068)

Component

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

Sample Rating Trend



DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Feb 2022	Feb2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCP55886	KCP05505197	
Sample Date		Client Info		10 Feb 2023	11 Feb 2022	
Machine Age	hrs	Client Info		3947	1707	
Oil Age	hrs	Client Info		2000	1707	
Oil Changed		Client Info		Not Changd	Changed	
Sample Status				ABNORMAL	ATTENTION	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	<1	<1	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	<1	<1	
Lead	ppm	ASTM D5185m	>10	<1	0	
Copper	ppm	ASTM D5185m	>50	2	1	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m	90	3	<1	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m	90	61	83	
Calcium	ppm	ASTM D5185m	2	1	<1	
Phosphorus	ppm	ASTM D5185m		3	3	
Zinc	ppm	ASTM D5185m		6	0	
Sulfur	ppm	ASTM D5185m		20108	17227	
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	1	<1	
Sodium	ppm	ASTM D5185m		20	13	
Potassium	ppm	ASTM D5185m	>20	6	10	
Water	%	ASTM D6304	>0.05	0.016	0.020	
ppm Water	ppm	ASTM D6304	>500	165.4	208.8	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		15238	4223	
Particles >6µm		ASTM D7647	>1300	^ 7509	945	
Particles >14µm		ASTM D7647	>80	629	A 86	
Particles >21µm		ASTM D7647	>20	<u> </u>	2 3	
Particles >38µm		ASTM D7647	>4	<u>^</u> 6	0	
Particles >71µm		ASTM D7647	>3	1	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u> </u>	▲ 17/14	
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.32	0.37	



OIL ANALYSIS REPORT

