

OIL ANALYSIS RE

GUAY SON [CONHER] **PERKINS IBACO Cozar XIX AUX 2** Component

Diesel Engine

Xtra Rev 15W40 (9 LTR)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor. (Customer Sample Comment: Please add particule count)

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of particulates present in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is acceptable for the time in service.


SIS REPC	ORT	Samp	le Rating Tre	end		ISO
(AUX 2				Feb2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KL0010240		
Sample Date		Client Info		22 Feb 2023		
Machine Age	hrs	Client Info		7750		
Oil Age	hrs	Client Info		50		
Oil Changed		Client Info		Not Changd		
Sample Status				ATTENTION		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Water		WC Method	>0.2	NEG		
Glycol		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>250	31		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m	>5	0		
Titanium	ppm	ASTM D5185m		<1		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>35	10		
Lead	ppm	ASTM D5185m	>100	<1		
Copper	ppm	ASTM D5185m	>60	2		
Tin	ppm	ASTM D5185m	>5	8		
Vanadium	ppm	ASTM D5185m		0		
	ppm	ASTM D5185m	11 and 10	0		
ADDITIVES		method	limit/base		history1	history2
Boron	ppm	ASTM D5185m		<1		
Barium Molybdenum	ppm	ASTM D5185m ASTM D5185m		<1 <1		
Manganese	ppm ppm	ASTM D5185m ASTM D5185m		<1 <1		
Magnesium	ppm	ASTM D5185m		<1 11		
Calcium	ppm	ASTM D5185m		3790		
Phosphorus	ppm	ASTM D5185m		1334		
Zinc	ppm	ASTM D5185m		1674		
	- Add					

Sulfur	ppm	ASTM D5185m		5222		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>35	9		
Sodium	ppm	ASTM D5185m		3		
Potassium	ppm	ASTM D5185m	>20	3		

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.1		
Nitration	Abs/cm	*ASTM D7624	>20	8.8		
Sulfation	Abs/.1mm	*ASTM D7415	>30	17.1		




OIL ANALYSIS REPORT









FLUID CLEANLIN	IESS	method	limit/base	current	history1	history
Particles >4µm		ASTM D7647		9248		
Particles >6µm		ASTM D7647	>5000	<mark>人</mark> 5038		
Particles >14µm		ASTM D7647	>640	<mark>人</mark> 857		
Particles >21µm		ASTM D7647	>160	<mark>人</mark> 289		
Particles >38µm		ASTM D7647	>40	<mark>人</mark> 45		
Particles >71µm		ASTM D7647	>10	5		
Oil Cleanliness		ISO 4406 (c)	>19/16	4 20/17		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	11.0		
Base Number (BN)	mg KOH/g	ASTM D2896		12.6		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
		*Visual	NORML	NORML		
Appearance Odor	scalar	*Visual				
Emulsified Water	scalar		NORML	NORML NEG		
Free Water	scalar	*Visual *Visual	>0.2	NEG		
	scalar			NEG		
FLUID PROPERT		method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445		13.1		
GRAPHS						
Ferrous Alloys			491,520	Particle Coun	t	T
30 iron						
20 - nickel			122,880	1		-2
10-			30,720	1		-2
2			S = 7.680		*** · · · ·	-2
Feb 22/23			Feb22/23 166'1 ml) 890 760'1 ml)			-1
—	-		프) 의미 11 480			1
Non-ferrous Metal	5		tied to	1		
copper			120 	1		
5 - tin			30)-		
				Bizverenal		
0				T		
Feb22/2:			Feb 22/2			
			ш (4μ 6μ	14µ 21µ	38µ 71µ
Viscosity @ 100°C				Base Numbe	r 	
Abnormal			S B S S			
			E10.0	1		
Abnormal			E 5.0	1		
Abnormal			2 Z			
			0.1 Base Number (mg KOH/d) Base 0.1			
			Feb22/23	Feb 22/23		

