

OIL ANALYSIS REPORT

Sample Rating Trend



VIS DEBRIS



KAESER 7078472

Component

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

Wear

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


		Feb-2021 Mm/2022 Mm/2023				
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCP53426	KCP44435	KCP34927
Sample Date		Client Info		04 May 2023	31 Mar 2022	25 Feb 2021
Machine Age	hrs	Client Info		7807	5358	2595
Oil Age	hrs	Client Info		2500	3000	2595
Oil Changed		Client Info		Not Changd	Changed	Changed
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	<1
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>3	<1	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	<1	<1	0
Lead	ppm	ASTM D5185m	>10	<1	0	0
Copper	ppm	ASTM D5185m	>50	22	13	18
Tin	ppm	ASTM D5185m	>10	<1	0	0
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	10
Barium	ppm	ASTM D5185m	90	0	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		<1	0	<1
Magnesium	ppm	ASTM D5185m	100	7	12	24
Calcium	ppm	ASTM D5185m	0	0	0	0
Phosphorus	ppm	ASTM D5185m	0	0	4	7
Zinc	ppm	ASTM D5185m	0	27	4	3
Sulfur	ppm	ASTM D5185m	23500	20883	17155	16553
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	3	<1	<1
Sodium	ppm	ASTM D5185m		6	2	7
Potassium	ppm	ASTM D5185m	>20	<1	2	2
Water	%	ASTM D6304	>0.05	0.007	0.011	0.009
ppm Water	ppm	ASTM D6304	>500	73.2	114.8	92.3
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647			12972	8099
Particles >6µm		ASTM D7647	>1300		▲ 3855	▲ 2360
Particles >14μm		ASTM D7647	>80		<u></u> 345	<u>^</u> 204
Particles >21µm		ASTM D7647	>20		<u></u> 101	<u></u> 470 € 70
Particles >38µm		ASTM D7647	>4		4	4
Particles >71µm		ASTM D7647	>3		0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13		<u> </u>	▲ 18/15
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.28	0.29	0.277


Page 1 of 2




OIL ANALYSIS REPORT












Color





GRAPHS

Bottom













Certificate L2367

Laboratory Sample No. Lab Number **Unique Number**

: KCP53426 : 05841509 : 10460312

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Recieved Diagnosed

: 08 May 2023 : 11 May 2023 Diagnostician : Don Baldridge Test Package : IND 2 (Additional Tests: KF, PrtCount)

BELNICK INC 4350 BALL GROUND HWY CANTON, GA US 30114 Contact: RHONDA KELLY

To discuss this sample report, contact Customer Service at 1-800-237-1369.

rhondakelly@theubiquegroup.com T:

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: BELCAN [WUSCAR] 05841509 (Generated: 02/07/2024 07:42:06) Rev: 1

Contact/Location: RHONDA KELLY - BELCAN

F: