




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
ADVANCED MIXER 189
 Component
Diesel Engine
 Fluid
DIESEL ENGINE OIL SAE 15W40 (10 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0802329	LP0000260	WC0661676
Sample Date	Client Info		05 May 2023	23 Jan 2023	26 Sep 2022
Machine Age	hrs	Client Info	40000	40000	40000
Oil Age	hrs	Client Info	500	500	500
Oil Changed	Client Info		Changed	Changed	Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >90	31	43	55
Chromium	ppm	ASTM D5185m >4	2	3	3
Nickel	ppm	ASTM D5185m >4	<1	0	0
Titanium	ppm	ASTM D5185m >2	0	0	0
Silver	ppm	ASTM D5185m >2	0	0	0
Aluminum	ppm	ASTM D5185m >15	4	1	2
Lead	ppm	ASTM D5185m >50	7	3	4
Copper	ppm	ASTM D5185m >55	<1	2	2
Tin	ppm	ASTM D5185m >4	2	1	1
Vanadium	ppm	ASTM D5185m	0	<1	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 250	21	6	10
Barium	ppm	ASTM D5185m 10	0	1	0
Molybdenum	ppm	ASTM D5185m 100	75	60	64
Manganese	ppm	ASTM D5185m	<1	<1	1
Magnesium	ppm	ASTM D5185m 450	863	955	908
Calcium	ppm	ASTM D5185m 3000	1478	1136	1149
Phosphorus	ppm	ASTM D5185m 1150	1182	1044	1042
Zinc	ppm	ASTM D5185m 1350	1507	1262	1270
Sulfur	ppm	ASTM D5185m 4250	4720	3334	3512

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >15	4	4	5
Sodium	ppm	ASTM D5185m >158	3	3	0
Potassium	ppm	ASTM D5185m >20	<1	<1	1

INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >6	1	1.9	2.4
Nitration	Abs/cm	*ASTM D7624 >20	10.6	10.1	11.3
Sulfation	Abs/.1mm	*ASTM D7415 >30	21.3	23.1	25.6

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	16.9	16.9	18.6
Base Number (BN)	mg KOH/g	ASTM D2896 8.5	9.56	10.36	8.77











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	13.3	13.79	13.8

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0802329 **Received** : 12 May 2023
Lab Number : 05846418 **Diagnosed** : 15 May 2023
Unique Number : 10470525 **Diagnostician** : Wes Davis
Test Package : MOB 2

TRESCA BROS SAND & GRAVEL INC
 66 MAIN ST
 MILLIS, MA
 US 02054
 Contact: FRAN ROSSI
 frossi@trescaconcrete.com
 T: (508)376-2957
 F: (508)376-4333

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)