




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
4572
 Component
Hydraulic System
 Fluid
NOT GIVEN (400 LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	WC0743525	WC0743529	---
Sample Date	Client Info	13 May 2023	18 Feb 2023	---
Machine Age	hrs Client Info	1115	266	---
Oil Age	hrs Client Info	1115	266	---
Oil Changed	Client Info	N/A	Not Changd	---
Sample Status		NORMAL	NORMAL	---

WEAR METALS

method	limit/base	current	history1	history2
Iron ppm ASTM D5185m	>20	<1	0	---
Chromium ppm ASTM D5185m	>20	0	0	---
Nickel ppm ASTM D5185m	>20	0	0	---
Titanium ppm ASTM D5185m		0	0	---
Silver ppm ASTM D5185m		0	0	---
Aluminum ppm ASTM D5185m	>20	0	0	---
Lead ppm ASTM D5185m	>20	0	0	---
Copper ppm ASTM D5185m	>20	0	<1	---
Tin ppm ASTM D5185m	>20	0	0	---
Vanadium ppm ASTM D5185m		0	0	---
Cadmium ppm ASTM D5185m		0	0	---

ADDITIVES

method	limit/base	current	history1	history2
Boron ppm ASTM D5185m		2	0	---
Barium ppm ASTM D5185m		0	0	---
Molybdenum ppm ASTM D5185m		<1	0	---
Manganese ppm ASTM D5185m		0	0	---
Magnesium ppm ASTM D5185m		<1	0	---
Calcium ppm ASTM D5185m		112	109	---
Phosphorus ppm ASTM D5185m		356	317	---
Zinc ppm ASTM D5185m		448	392	---
Sulfur ppm ASTM D5185m		8539	7680	---

CONTAMINANTS

method	limit/base	current	history1	history2
Silicon ppm ASTM D5185m	>15	6	6	---
Sodium ppm ASTM D5185m		0	<1	---
Potassium ppm ASTM D5185m	>20	0	0	---

FLUID CLEANLINESS





method	limit/base	current	history1	history2
Particles >4µm ASTM D7647	>5000	2423	1268	---
Particles >6µm ASTM D7647	>1300	870	467	---
Particles >14µm ASTM D7647	>160	97	38	---
Particles >21µm ASTM D7647	>40	26	6	---
Particles >38µm ASTM D7647	>10	1	1	---
Particles >71µm ASTM D7647	>3	0	0	---
Oil Cleanliness ISO 4406 (c)	>19/17/14	18/17/14	17/16/12	---

FLUID DEGRADATION

method	limit/base	current	history1	history2
Acid Number (AN) mg KOH/g ASTM D8045		0.61	0.60	---




OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.05	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	62.4	62.4	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0743525 **Received** : 17 May 2023
Lab Number : 05850169 **Diagnosed** : 22 May 2023
Unique Number : 10479524 **Diagnostician** : Jonathan Hester
Test Package : PLANT

EFACTOR3 LLC
 15050 CHOATE CIR, SUITE E
 CHARLOTTE, NC
 US 28273
 Contact: L. REID
 LREID@EFACTOR3.COM
 T:
 F: (704)944-3234

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)