


OIL ANALYSIS REPORT

Sample Rating Trend







Area 9 Machine Id WTG-906 Component

Hydraulic System

SHELL TELLUS 32 (300 LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Sep2016 Ming2017 Nov2017 Jus2018 Feb2019 Nov2019 Jus2020 Ming2021 Feb2022 Ming2023						
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0804512	WC05504468	WC0547237
Sample Date		Client Info		25 May 2023	02 Feb 2022	10 Mar 2021
Machine Age	mths	Client Info		0	69	120
Oil Age	mths	Client Info		0	5	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184		12	20	
Iron	ppm	ASTM D5185m	>20	11	10	11
Chromium	ppm	ASTM D5185m	>20	9	8	10
Nickel	ppm	ASTM D5185m	>20	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	<1	0
Aluminum	ppm	ASTM D5185m	>20	<1	0	0
Lead	ppm	ASTM D5185m	>20	0	0	<1
Copper	ppm	ASTM D5185m	>20	2	3	3
Tin	ppm	ASTM D5185m	>20	<1	0	<1
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		<1	<1	<1
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	11	19	9	7
Calcium	ppm	ASTM D5185m	35	25	27	26
Phosphorus	ppm	ASTM D5185m	259	280	281	265
Zinc	ppm	ASTM D5185m	277	293	262	255
Sulfur	ppm	ASTM D5185m	1865	3531	3368	4141
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	<1	<1
Sodium	ppm	ASTM D5185m		1	0	0
Potassium	ppm	ASTM D5185m	>20	<1	0	<1
Water	%	ASTM D6304	>0.05	0.004	0.010	0.014
ppm Water	ppm	ASTM D6304	>500	44.3	108.8	147.5
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	198	4536	4276
Particles >6µm		ASTM D7647	>1300	35	1078	1031
Particles >14µm		ASTM D7647	>160	4	123	92
Particles >21µm		ASTM D7647	>40	1	36	24
Particles >38µm		ASTM D7647	>10	0	4	4
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>19/17/14	15/12/9	19/17/14	19/17/14



OIL ANALYSIS REPORT







Certificate L2367

Lab Number **Unique Number**

: 05857904 : 10492369

Diagnosed Diagnostician

: 30 May 2023 : Jonathan Hester Test Package : IND 2 (Additional Tests: KF, PQ)

FRANCISCO MORAZAN, ZZ

HN Contact: SANTOS DEL CID

sdelcid@dencmi.com

T: x: F: x:

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

To discuss this sample report, contact Customer Service at 1-800-237-1369.