

OIL ANALYSIS REPORT

Sample Rating Trend







Area 5 Machine Id WTG-501 Component

Hydraulic System

SHELL TELLUS 32 (300 LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

0±2015 Apr2017 Nov2017 Jus2018 Feb2019 0±2019 Jus2020 Mu±2021 Jus2022 Mu±2023						
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0804524	WC05504453	WC0547171
Sample Date		Client Info		02 Mar 2023	27 Jan 2022	03 Mar 2021
Machine Age	mths	Client Info		0	0	120
Oil Age	mths	Client Info		0	5	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184		12	17	
Iron	ppm	ASTM D5185m	>20	3	2	2
Chromium	ppm	ASTM D5185m	>20	6	6	4
Nickel	ppm	ASTM D5185m	>20	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	<1	0
Aluminum	ppm	ASTM D5185m	>20	<1	0	0
Lead	ppm	ASTM D5185m	>20	0	0	<1
Copper	ppm	ASTM D5185m	>20	<1	1	1
Tin	ppm	ASTM D5185m	>20	<1	0	0
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m	11	3	7	2
Calcium	ppm	ASTM D5185m	35	17	26	26
Phosphorus	ppm	ASTM D5185m	259	289	287	265
Zinc	ppm	ASTM D5185m	277	323	294	297
Sulfur	ppm	ASTM D5185m	1865	1642	1755	1957
CONTAMINANTS						
)	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	limit/base >15	<1	history1	<1
Sodium		ASTM D5185m ASTM D5185m	>15	<1 <1		<1
Sodium Potassium	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	>15 >20	<1 <1 <1	0 0 0	<1 0 <1
Sodium Potassium Water	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D6304	>15 >20 >0.05	<1 <1 <1 0.007	0 0 0 0.004	<1 0 <1 0.007
Sodium Potassium Water ppm Water	ppm ppm ppm % ppm	ASTM D5185m ASTM D5185m ASTM D5185m	>15 >20 >0.05 >500	<1 <1 <1	0 0 0 0.004 49.6	<1 0 <1 0.007 74.3
Sodium Potassium Water ppm Water FLUID CLEANLIN	ppm ppm ppm % ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 method	>15 >20 >0.05	<1 <1 <1 0.007 74.0 current	0 0 0 0.004 49.6 history1	<1 0 <1 0.007 74.3 history2
Sodium Potassium Water ppm Water FLUID CLEANLIN Particles >4µm	ppm ppm ppm % ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 method ASTM D7647	>15 >20 >0.05 >500 limit/base	<1 <1 <1 0.007 74.0 current	0 0 0 0.004 49.6 history1	<1 0 <1 0.007 74.3 history2 2128
Sodium Potassium Water ppm Water FLUID CLEANLIN Particles >4µm Particles >6µm	ppm ppm ppm % ppm	ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 ASTM D6304 method ASTM D7647 ASTM D7647	>15 >20 >0.05 >500 limit/base	<1 <1 <1 0.007 74.0 current 261 71	0 0 0 0.004 49.6 history1 1545 285	<1 0 <1 0.007 74.3 history2 2128 657
Sodium Potassium Water ppm Water FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm	ppm ppm ppm % ppm	ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 ASTM D6304 method ASTM D7647 ASTM D7647 ASTM D7647	>15 >20 >0.05 >500 limit/base >5000 >640	<1 <1 <1 0.007 74.0 current 261 71 11	0 0 0 0.004 49.6 history1 1545 285 25	<1 0 <1 0.007 74.3 history2 2128 657 76
Sodium Potassium Water ppm Water FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm	ppm ppm ppm % ppm	ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 ASTM D6304 method ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>15 >20 >0.05 >500 limit/base >5000 >640 >160	<1 <1 <1 0.007 74.0 current 261 71 11 4	0 0 0 0.004 49.6 history1 1545 285 25	<1 0 <1 0.007 74.3 history2 2128 657 76 22
Sodium Potassium Water ppm Water FLUID CLEANLIN Particles >4µm Particles >6µm Particles >21µm Particles >38µm	ppm ppm ppm % ppm	ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 Method ASTM D7647	>15 >20 >0.05 >500 limit/base >5000 >640 >160 >40	<1 <1 <1 <1 0.007 74.0 current 261 71 11 4 1	0 0 0 0.004 49.6 history1 1545 285 25 9	<1 0 <1 0.007 74.3 history2 2128 657 76 22 2
Sodium Potassium Water ppm Water FLUID CLEANLIN Particles >4µm Particles >6µm Particles >14µm Particles >21µm	ppm ppm ppm % ppm	ASTM D5185m ASTM D5185m ASTM D6304 ASTM D6304 ASTM D6304 method ASTM D7647 ASTM D7647 ASTM D7647 ASTM D7647	>15 >20 >0.05 >500 limit/base >5000 >640 >160	<1 <1 <1 0.007 74.0 current 261 71 11 4	0 0 0 0.004 49.6 history1 1545 285 25	<1 0 <1 0.007 74.3 history2 2128 657 76 22



OIL ANALYSIS REPORT







Certificate L2367

Sample No. Lab Number **Unique Number**

: 05857964

: WC0804524 : 10492429

Diagnosed Diagnostician Test Package : IND 2 (Additional Tests: KF, PQ)

: 30 May 2023 : Don Baldridge FRANCISCO MORAZAN, ZZ

Contact: SANTOS DEL CID sdelcid@dencmi.com

T: x: F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

HN