

OIL ANALYSIS REPORT

Sample Rating Trend

ISO

7879670 (S/N 1215)

Component

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Jun 2022	May2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info	minu bass	KCPA003895	KCP41384	
Sample Date		Client Info		30 May 2023	24 Jun 2022	
Machine Age	hrs	Client Info		4124	527	
Oil Age	hrs	Client Info		0	527	
Oil Changed	1110	Client Info		N/A	Changed	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	1	
Chromium	ppm		>10	0	0	
Nickel	ppm	ASTM D5185m	>3	<1	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m		0	<1	
Lead	ppm	ASTM D5185m	>10	0	<1	
Copper	ppm	ASTM D5185m		13	<1	
Tin	ppm	ASTM D5185m	>10	<1	0	
Vanadium	ppm	ASTM D5185m	7.0	0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES	1-1-	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	1	
Barium	ppm	ASTM D5185m	90	28	37	
Molybdenum		ASTM D5185m	0	0	0	
Manganese	ppm	ASTM D5185m	U	<1	<1	
Magnesium		ASTM D5185m	100	35	72	
Calcium	ppm	ASTM D5185m	0	აა 1	12	
Phosphorus		ASTM D5185m	0	3	7	
Zinc	ppm	ASTM D5185m	0	0	6	
Sulfur	ppm	ASTM D5185m	23500	23342	18566	
	ppm					
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	1	<1	
Sodium	ppm	ASTM D5185m		3	7	
Potassium	ppm	ASTM D5185m	>20	2	4	
Water	%	ASTM D6304	>0.05	0.015	0.016	
ppm Water	ppm	ASTM D6304	>500	154.7	168.0	
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		23945	10316	
Particles >6µm		ASTM D7647		<u>^</u> 7176	▲ 3808	
Particles >14µm		ASTM D7647	>80	<u>▲</u> 571	<u> 161</u>	
Particles >21μm		ASTM D7647	>20	<u> </u>	<u>^</u> 22	
Particles >38μm		ASTM D7647	>4	4	1	
Particles >71μm		ASTM D7647		0	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>22/20/16</u>	<u>\$\text{\Delta}\$</u> 21/19/15	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.33	0.39	



OIL ANALYSIS REPORT

