




PROBLEM SUMMARY

Sample Rating Trend



VIS DEBRIS



Machine Id
4047602 (S/N 6667)

Component
Compressor
Fluid
KAESER SIGMA (OEM) M-460 (--- GAL)

COMPONENT CONDITION SUMMARY

No relevant graphs to display

RECOMMENDATION

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

PROBLEMATIC TEST RESULTS

| Sample Status | | | | ABNORMAL | ABNORMAL | ABNORMAL |
|---------------|--------|---------|------|-----------------|----------|----------|
| Debris | scalar | *Visual | NONE | ▲ MODER | ▲ MODER | NONE |

Customer Id: EASCONCA
Sample No.: KCPA002330
Lab Number: 05879565
Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data:
Don Baldrige +1
don.b505@comcast.net

To change component or sample information:
Customer Service +1 1-800-237-1369
customerservice@wearcheck.com

RECOMMENDED ACTIONS

| Action | Status | Date | Done By | Description |
|--------|--------|------|---------|---|
| Alert | --- | --- | ? | We were unable to perform a particle count due to a high concentration of particles present in this sample. |

HISTORICAL DIAGNOSIS

20 Apr 2022 Diag: Doug Bogart

VIS DEBRIS



No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample. All component wear rates are normal. Moderate concentration of visible dirt/debris present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

view report



14 Mar 2022 Diag: Angela Borella

ISO



No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. All component wear rates are normal. There is a high amount of particulates present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

view report



25 Jan 2021 Diag: Don Baldrige

WEAR




No corrective action is recommended at this time. Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor. The iron level is abnormal. All other component wear rates are normal. There is a high amount of particulates present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

view report



OIL ANALYSIS REPORT

Sample Rating Trend



VIS DEBRIS



Machine Id
4047602 (S/N 6667)

Component
Compressor
Fluid
KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

▲ Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

Wear

All component wear rates are normal.

▲ Contamination

Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

| | method | limit/base | current | history1 | history2 |
|---------------|-------------|-------------|--------------------|-------------|-------------|
| Sample Number | Client Info | | KCPA002330 | KCP44250 | KCP38402 |
| Sample Date | Client Info | | 15 Jun 2023 | 20 Apr 2022 | 14 Mar 2022 |
| Machine Age | hrs | Client Info | 60756 | 54016 | 53871 |
| Oil Age | hrs | Client Info | 0 | 0 | 3000 |
| Oil Changed | Client Info | | N/A | Changed | Changed |
| Sample Status | | | ABNORMAL | ABNORMAL | ABNORMAL |

WEAR METALS

| | method | limit/base | current | history1 | history2 |
|----------|--------|-----------------|--------------|----------|----------|
| Iron | ppm | ASTM D5185m >50 | <1 | 4 | 2 |
| Chromium | ppm | ASTM D5185m >10 | 0 | 0 | 0 |
| Nickel | ppm | ASTM D5185m >3 | <1 | 0 | 0 |
| Titanium | ppm | ASTM D5185m >3 | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185m >2 | 0 | <1 | <1 |
| Aluminum | ppm | ASTM D5185m >10 | <1 | <1 | <1 |
| Lead | ppm | ASTM D5185m >10 | 0 | <1 | 0 |
| Copper | ppm | ASTM D5185m >50 | 8 | 9 | 22 |
| Tin | ppm | ASTM D5185m >10 | 0 | 0 | 0 |
| Antimony | ppm | ASTM D5185m | --- | --- | --- |
| Vanadium | ppm | ASTM D5185m | 0 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | 0 | 0 | 0 |

ADDITIVES

| | method | limit/base | current | history1 | history2 |
|------------|--------|-------------------|--------------|----------|----------|
| Boron | ppm | ASTM D5185m 0 | 0 | 0 | 2 |
| Barium | ppm | ASTM D5185m 90 | 2 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m 0 | 0 | 0 | 0 |
| Manganese | ppm | ASTM D5185m | 0 | 2 | <1 |
| Magnesium | ppm | ASTM D5185m 100 | <1 | 56 | 3 |
| Calcium | ppm | ASTM D5185m 0 | 0 | 0 | 0 |
| Phosphorus | ppm | ASTM D5185m 0 | 5 | 4 | 0 |
| Zinc | ppm | ASTM D5185m 0 | 0 | 27 | 55 |
| Sulfur | ppm | ASTM D5185m 23500 | 18601 | 16480 | 15617 |

CONTAMINANTS

| | method | limit/base | current | history1 | history2 |
|-----------|--------|------------------|--------------|----------|----------|
| Silicon | ppm | ASTM D5185m >25 | 3 | <1 | <1 |
| Sodium | ppm | ASTM D5185m | 0 | 8 | 2 |
| Potassium | ppm | ASTM D5185m >20 | <1 | 4 | 0 |
| Water | % | ASTM D6304 >0.05 | 0.010 | 0.018 | 0.003 |
| ppm Water | ppm | ASTM D6304 >500 | 100.5 | 180.1 | 37.2 |




FLUID CLEANLINESS

| | method | limit/base | current | history1 | history2 |
|-----------------|--------------|------------|------------|----------|----------|
| Particles >4µm | ASTM D7647 | | --- | --- | 39369 |
| Particles >6µm | ASTM D7647 | >1300 | --- | --- | ▲ 7469 |
| Particles >14µm | ASTM D7647 | >80 | --- | --- | ▲ 424 |
| Particles >21µm | ASTM D7647 | >20 | --- | --- | ▲ 84 |
| Particles >38µm | ASTM D7647 | >4 | --- | --- | 5 |
| Particles >71µm | ASTM D7647 | >3 | --- | --- | 0 |
| Oil Cleanliness | ISO 4406 (c) | >--/17/13 | --- | --- | ▲ 20/16 |

FLUID DEGRADATION

| | method | limit/base | current | history1 | history2 |
|------------------|----------|----------------|-------------|----------|----------|
| Acid Number (AN) | mg KOH/g | ASTM D8045 1.0 | 0.48 | 0.40 | 0.41 |


OIL ANALYSIS REPORT







| VISUAL | method | limit/base | current | history1 | history2 |
|------------------|--------|------------|---------|----------|----------|
| White Metal | scalar | *Visual | NONE | NONE | NONE |
| Yellow Metal | scalar | *Visual | NONE | NONE | NONE |
| Precipitate | scalar | *Visual | NONE | NONE | NONE |
| Silt | scalar | *Visual | NONE | NONE | NONE |
| Debris | scalar | *Visual | ▲ MODER | ▲ MODER | NONE |
| Sand/Dirt | scalar | *Visual | NONE | NONE | NONE |
| Appearance | scalar | *Visual | NORML | NORML | NORML |
| Odor | scalar | *Visual | NORML | NORML | NORML |
| Emulsified Water | scalar | *Visual | >0.05 | NEG | NEG |
| Free Water | scalar | *Visual | | NEG | NEG |

| FLUID PROPERTIES | method | limit/base | current | history1 | history2 |
|------------------|--------|--------------|---------|----------|----------|
| Visc @ 40°C | cSt | ASTM D445 45 | 53.5 | 45.2 | 46.4 |

| SAMPLE IMAGES | method | limit/base | current | history1 | history2 |
|---------------|--------|------------|---------|----------|----------|
|---------------|--------|------------|---------|----------|----------|



GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : KCPA002330 **Received** : 21 Jun 2023
Lab Number : 05879565 **Diagnosed** : 23 Jun 2023
Unique Number : 10524668 **Diagnostician** : Don Baldrige
Test Package : IND 2 (Additional Tests: KF, PrtCount)

EAST BAY MACHINE - AMADA AMERICA
 1030 SHARY CT
 CONCORD, CA
 US 94518
 Contact: SEAN MECLELLAN
 sean.meclellan@eastbaymachine.com

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:
F: