

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id **PIERCE 114** Component Hydraulic System Fluid NOT GIVEN (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The condition of the oil is acceptable for the time in service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0826469	WC0572781	WC0473005
Sample Date		Client Info		01 Jul 2023	09 Jul 2021	15 Jul 2020
Machine Age	hrs	Client Info		2347	0	0
Oil Age	hrs	Client Info		2347	0	0
Oil Changed		Client Info		N/A	Not Changd	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	<1	<1	1
Chromium	ppm	ASTM D5185m	>10	0	0	<1
Nickel	ppm	ASTM D5185m	>10	<1	0	<1
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	0	0
Lead	ppm	ASTM D5185m		<1	0	0
Copper	ppm	ASTM D5185m		5	5	4
Tin	ppm	ASTM D5185m		0	0	0
Antimony	ppm	ASTM D5185m			0	5
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		1	1	1
ADDITIVES	ppm	method	limit/base	current	history1	history2
			iinii/base		5	
Boron	ppm	ASTM D5185m		0		1
Barium	ppm	ASTM D5185m		-	0	<1
Molybdenum	ppm	ASTM D5185m		<1	<1	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m		0	0	1
Calcium	ppm	ASTM D5185m		156	155	152
Phosphorus	ppm	ASTM D5185m		659	628	634
Zinc	ppm	ASTM D5185m		875	838	790
Sulfur	ppm	ASTM D5185m		3040	2421	2247
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	<1	0	2
Sodium	ppm	ASTM D5185m		<1	2	2
Potassium	ppm	ASTM D5185m	>20	1	0	<1
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG



OIL ANALYSIS REPORT



Visc @ 40°C SAMPLE IMAGE Color Bottom GRAPHS Ferrous Alloys	cSt	ASTM D445 method	limit/base	45.6 current no image no image	45.8 history1 no image no image	45.5 histo no ima no ima
Color Bottom GRAPHS Ferrous Alloys	S	method	limit/base	no image	no image	no ima
Bottom GRAPHS Ferrous Alloys						
GRAPHS Ferrous Alloys				no image	no image	no ima
Ferrous Alloys						
Ferrous Alloys						
9 8 7 6						
4						
3 2 1 0 8///1 5/5	15/20	ul9/21	u1/23			
		٦u	٦٢			
10 g copper						
8 - management lead						
6						
4						
3 - 2						
1			and a state of the			
p17/18	ul15/20 -	Jul9/21.	Jul1/23 4			
ی Viscosity @ 40°C	7					
52 Abnormal	I I	·				
48						
44 -						
42 - Abnomal						
38 4 81//11	15/20 +	u19/21+	11/23			
: WearCheck USA - : WC0826469 : 05899107 : 10560463	501 Madia Received Diagnos	25 E CHERF NORTH LIBER US S				
	Non-ferrous Meta Non-ferrous Meta Copper Super Viscosity @ 40°C Abnormal Super Viscosity @ 40°C Copper Super Viscosity @ 40°C Copper Supe	Non-ferrous Metals Non-ferrous Metals Viscosity @ 40°C Abnomal WearCheck USA - 501 Madia WC0826469 Received 05899107 Diagnost 10560463 Diagnost FLEET ontact Customer Service at 1-8	Non-ferrous Metals Non-ferrous Metals	Non-ferrous Metals Non-ferrous Metals Non-ferrous Metals Viscosity @ 40°C Viscosity @ 40°C Viscosity @ 40°C Viscosity @ 40°C Viscosity @ 40°C MearCheck USA - 501 Madison Ave., Cary, NC 27513 WC0826469 Received : 14 Jul 2023 US6899107 Diagnosed : 17 Jul 2023 Diagnoset : 17 Jul 2023 Diagnostician : Wes Davis FLEET mtact Customer Service at 1-800-237-1369.	Non-ferrous Metals	Non-ferrous Metals Non-ferrous Metals Non-ferrous Metals Viscosity @ 40°C WearCheck USA - 501 Madison Ave., Cary, NC 27513 WearCheck USA -

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)