

PROBLEM SUMMARY

KAESER AIRCENTER SM15 6239898 (S/N 1061)

Compressor



COMPONENT CONDITION SUMMARY



RECOMMENDATION

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

PROBLEMATIC T	EST RE	SULTS				
Sample Status				ABNORMAL	NORMAL	ABNORMAL
Magnesium	ppm	ASTM D5185m	100	A 37	51	47
Particles >14µm		ASTM D7647	>80	4 95	68	
Particles >21µm		ASTM D7647	>20	A 36	22	
Oil Cleanliness		ISO 4406 (c)	>/17/13	 19/17/14	18/17/13	

Customer Id: CHEBEE Sample No.: KCPA004502 Lab Number: 05899343 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Jonathan Hester +1 919-379-4092 x4092 <u>jhester@wearcheckusa.com</u>

To change component or sample information: Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u>



RECOMMENDED ACTIONS

There are no recommended actions for this sample.

HISTORICAL DIAGNOSIS

08 Dec 2022 Diag: Don Baldridge



Resample at the next service interval to monitor.All component wear rates are normal. The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

31 Mar 2022 Diag: Angela Borella



No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.All component wear rates are normal. Moderate concentration of visible dirt/debris present in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for





09 Sep 2021 Diag: Don Baldridge

further service.







Report Id: CHEBEE [WUSCAR] 05899343 (Generated: 07/18/2023 17:36:08) Rev: 1



OIL ANALYSIS REPORT

Machine Id KAESER AIRCENTER SM15 6239898 (S/N 1061) Component

Compressor Fluid

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA004502	KCP52075	KCP44320
Sample Date		Client Info		05 Jul 2023	08 Dec 2022	31 Mar 2022
Machine Age	hrs	Client Info		20343	34154	31152
Oil Age	hrs	Client Info		0	4825	3656
Oil Changed		Client Info		N/A	Changed	Not Changd
Sample Status				ABNORMAL	NORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	mqq	ASTM D5185m	>50	0	<1	1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	<1	0
Aluminum	ppm	ASTM D5185m	>10	<1	<1	3
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	8	10	6
Tin	ppm	ASTM D5185m	>10	0	0	0
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	<1
Barium	ppm	ASTM D5185m	90	0	5	26
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	100	A 37	51	47
Calcium	ppm	ASTM D5185m	0	0	0	0
Phosphorus	ppm	ASTM D5185m	0	5	<1	31
Zinc	ppm	ASTM D5185m	0	24	42	4
Sulfur	ppm	ASTM D5185m	23500	21448	25532	11875
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	2	1
Sodium	ppm	ASTM D5185m		12	7	6
Potassium	ppm	ASTM D5185m	>20	2	2	<1
Water	%	ASTM D6304	>0.05	0.020	0.021	0.012
ppm Water	ppm	ASTM D6304	>500	203.1	217.9	121.2
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		2965	2194	
Particles >6µm		ASTM D7647	>1300	795	728	
Particles >14µm		ASTM D7647	>80	▲ 95	68	
Particles >21µm		ASTM D7647	>20	<u> </u>	22	
Particles >38µm		ASTM D7647	>4	1	1	
Particles >71µm		ASTM D7647	>3	0	0	
OII Cleanliness		ISO 4406 (c)	>/17/13	<u> </u>	18/17/13	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	ma KOH/a	ASTM D8045	1.0	0.33	0.52	0.34

Acid Number (AN) Report Id: CHEBEE [WUSCAR] 05899343 (Generated: 07/18/2023 17:36:08) Rev: 1

mg KOH/g ASTM D8045 1.0

0.33 0.52

Contact/Location: TRAVIS ALLEN - CHEBEE



70 60k

E 50k

30k

년 20k

10

٧ 1.20

à 0.96

Δ 1.20

0.72<u>ه</u>

2²0.48

0.24 0.00

f narticles 40k

OIL ANALYSIS REPORT

article	Trend					VISUAI	
	ŧμm Sum					White Metal	s
	4μm					Yellow Metal	S
						Precipitate	S
						Silt	5
No.						Debris	5
	1					Sand/Dirt	S
	3/20	9/21	1/22	8/22	5/23	Appearance	S
	Api	Set	Mar3	Dec	Jul	Odor	5
ator						Emulsified Water	5
						Free Water	S
vere						FLUID PROPER	TIE
						Visc @ 40°C	(
						SAMPLE IMAGE	S
bnormal							
	or3/20	sp 9/21	31/22	c8/22	ul5/23	Color	
	Aş	ŏ	Mar	De	'n		
cid Nu	mber						





Contact/Location: TRAVIS ALLEN - CHEBEE