

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Mixing Banbury Drop Mills **BB03DM (S/N TPK-093)** Component

Inboard Bearing

R&O OIL ISO 68 (1 GAL)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the

Fluid Condition

The condition of the oil is acceptable for the time in service.

		g2009 Feb20	011 Jul2012 Mar2015	Feb 2017 Jul 2019 Mar 2021	Jul2022	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0811655	WC0728288	WC0680135
Sample Date		Client Info		07 Jul 2023	13 Dec 2022	12 Jul 2022
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	0	<1	<1
Chromium	ppm	ASTM D5185m	>20	0	0	0
Nickel	ppm	ASTM D5185m	>20	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>20	<1	0	<1
Lead	ppm	ASTM D5185m	>20	0	0	0
Copper	ppm	ASTM D5185m	>20	<1	<1	<1
Tin	ppm	ASTM D5185m	>20	7	13	11
Vanadium	ppm	ASTM D5185m		<1	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	5	0	0	0
Barium	ppm	ASTM D5185m	5	0	0	4
Molybdenum	ppm	ASTM D5185m	5	0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	5	<1	0	0
Calcium	ppm	ASTM D5185m	5	0	0	<1
Phosphorus	ppm	ASTM D5185m	100	7	27	6
Zinc	ppm	ASTM D5185m	25	0	0	3
Sulfur	ppm	ASTM D5185m	1500	2126	1853	2044
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	<1	0
Sodium	ppm	ASTM D5185m		0	0	0
Potassium	ppm	ASTM D5185m	>20	0	0	0
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2

Visc @ 40°C


cSt

ASTM D445 68

68.2



OIL ANALYSIS REPORT





GRAPHS Ferrous Alloys 35 25 · 10 Non-ferrous Metals 400 350 300 250 E. 200 150 100 Viscosity @ 40°C 72 \$ 66 60 58





Certificate L2367

Laboratory Sample No. Lab Number Test Package : IND 1

: 05899477 Unique Number : 10560833

To discuss this sample report, contact Customer Service at 1-800-237-1369.

: WC0811655

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 14 Jul 2023 Diagnosed : 18 Jul 2023 Diagnostician : Angela Borella

SIEMENS INDUSTRY INC. 4140 E. FRONT ST. KANSAS CITY, MO

US 64120 Contact: Dave Wisemore

david.wisemore@siemens.com T: (816)241-5544

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: SIEKAN [WUSCAR] 05899477 (Generated: 07/18/2023 18:28:53) Rev: 1

Submitted By: Dave Wisemore

F: x: