

# **OIL ANALYSIS REPORT**

# Sample Rating Trend

## **NORMAL**


# Formulation-FHG

# Sew Euro Drive FHG56JB01 Standardization Tank, Agitator

Component

Gearbox

JAX FGG-AW ISO 220 (--- GAL)





### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

#### Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.


### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jan2020 Jul	12020 Dec2020 Jun2021	Dec2021 Jun2022 Dec2022 Jun2	023 Jui2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0808218	WC0782840	WC0663743
Sample Date		Client Info		13 Jul 2023	20 Jun 2023	06 Dec 2022
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ABNORMAL	ATTENTION
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	2	2	2
Chromium	ppm	ASTM D5185m	>15	0	0	0
Nickel	ppm	ASTM D5185m	>15	0	0	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	<1	2
Lead	ppm	ASTM D5185m	>100	0	0	0
Copper	ppm	ASTM D5185m	>200	0	0	0
Tin	ppm	ASTM D5185m	>25	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		4	0	<1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m		0	0	<1
Calcium	ppm	ASTM D5185m		2	0	3
Phosphorus	ppm	ASTM D5185m		596	487	459
Zinc	ppm	ASTM D5185m		<1	0	11
Sulfur	ppm	ASTM D5185m		881	400	238
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	4	7	6
Sodium	ppm	ASTM D5185m		<1	1	<1
Potassium	ppm	ASTM D5185m	>20	<1	0	0
Water	%	ASTM D6304	>0.2	0.010	0.005	0.011
ppm Water	ppm	ASTM D6304		105.6	59.0	117.0
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	12022		<u> </u>
Particles >6µm		ASTM D7647	>5000	2045		△ 5062
Particles >14µm		ASTM D7647	>640	55		251
Particles >21µm		ASTM D7647	>160	14		22
Particles >38µm		ASTM D7647	>40	1		1
Particles >71µm		ASTM D7647	>10	0		0
Oil Cleanliness		ISO 4406 (c)	>21/19/16	21/18/13		<b>22/20/15</b>
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.68	0.63	0.65



# **OIL ANALYSIS REPORT**



\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (919)494-3146

F: (919)494-3456