


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



7218603 (S/N 1219)

Component

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.

| | | | May2021 | Jul2023 | | |
|-----------------|--------|--------------|------------|-------------|----------------|----------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | KCP35058 | KCP30065 | |
| Sample Date | | Client Info | | 10 Jul 2023 | 27 May 2021 | |
| Machine Age | hrs | Client Info | | 17258 | 6083 | |
| Oil Age | hrs | Client Info | | 1 | 4000 | |
| Oil Changed | | Client Info | | Changed | Changed | |
| Sample Status | | | | NORMAL | ABNORMAL | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| ron | ppm | ASTM D5185m | >50 | 0 | 0 | |
| Chromium | ppm | ASTM D5185m | >10 | 0 | 0 | |
| Nickel | ppm | ASTM D5185m | >3 | <1 | 0 | |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | |
| Silver | ppm | ASTM D5185m | >2 | 0 | <1 | |
| Aluminum | ppm | ASTM D5185m | >10 | 0 | 0 | |
| Lead | ppm | ASTM D5185m | >10 | 0 | 0 | |
| Copper | ppm | | >50 | 5 | 9 | |
| Soppei Tin | | ASTM D5185m | >10 | 0 | 0 | |
| | ppm | | >10 | | 0 | |
| Antimony | ppm | ASTM D5185m | | | | |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | 0 | 0 | <1 | |
| Barium | ppm | ASTM D5185m | 90 | 0 | 0 | |
| Molybdenum | ppm | ASTM D5185m | 0 | 0 | 0 | |
| Manganese | ppm | ASTM D5185m | | 0 | 0 | |
| Magnesium | ppm | ASTM D5185m | 100 | 0 | 0 | |
| Calcium | ppm | ASTM D5185m | 0 | 0 | 0 | |
| Phosphorus | ppm | ASTM D5185m | 0 | 0 | 10 | |
| Zinc | ppm | ASTM D5185m | 0 | 0 | 0 | |
| Sulfur | ppm | ASTM D5185m | 23500 | 11809 | 9961 | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | 0 | <1 | |
| Sodium | ppm | ASTM D5185m | | 0 | 0 | |
| Potassium | ppm | ASTM D5185m | >20 | 1 | <1 | |
| Water | % | ASTM D6304 | >0.05 | 0.004 | 0.007 | |
| opm Water | ppm | ASTM D6304 | >500 | 48.8 | 71.8 | |
| FLUID CLEANLIN | ESS | method | limit/base | current | history1 | history2 |
| Particles >4μm | | ASTM D7647 | | 485 | 12382 | |
| Particles >6µm | | ASTM D7647 | >1300 | 194 | ▲ 4875 | |
| Particles >14μm | | ASTM D7647 | >80 | 15 | 55 | |
| Particles >21μm | | ASTM D7647 | >20 | 5 | 8 | |
| Particles >38µm | | ASTM D7647 | >4 | 0 | 0 | |
| Particles >71μm | | ASTM D7647 | >3 | 0 | 0 | |
| Oil Cleanliness | | ISO 4406 (c) | >/17/13 | 16/15/11 | △ 19/13 | |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| | | | | | | |

0.49



OIL ANALYSIS REPORT

