

OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



DT-102
Component

Swing Drive

GEAR OIL SAE 85W140 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Moor

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil

Fluid Condition

The condition of the oil is acceptable for the time in service.

		,		May2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0705202		
Sample Date		Client Info		26 May 2023		
Machine Age	hrs	Client Info		1049		
Oil Age	hrs	Client Info		1049		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
ron	ppm	ASTM D5185m	>400	202		
Chromium	ppm	ASTM D5185m	>10	4		
Nickel	ppm	ASTM D5185m	>10	0		
Γitanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	1		
_ead	ppm	ASTM D5185m	>50	0		
Copper	ppm	ASTM D5185m	>200	17		
-in	ppm	ASTM D5185m	>10	0		
/anadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	400	0		
Barium	ppm	ASTM D5185m	200	9		
Nolybdenum	ppm	ASTM D5185m	12	<1		
Manganese	ppm	ASTM D5185m		5		
Magnesium	ppm	ASTM D5185m	12	7		
Calcium	ppm	ASTM D5185m	150	666		
Phosphorus	ppm	ASTM D5185m	1650	784		
Zinc	ppm	ASTM D5185m	125	207		
Sulfur	ppm	ASTM D5185m	22500	32241		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	15		
Sodium	ppm	ASTM D5185m		6		
Potassium	ppm	ASTM D5185m	>20	<1		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	LIGHT		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual	/U.L	NEG		
FLUID PROPERT	IES	method				history2

Visc @ 40°C

cSt


ASTM D445 368

Report Id: ECPROA [WUSCAR] 05901617 (Generated: 07/20/2023 12:43:22) Rev: 1

Contact/Location: EDDIE SECO - ECPROA





OIL ANALYSIS REPORT






GRAPHS









Laboratory Sample No. Lab Number Unique Number : 10562973

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : WC0705202 : 05901617

Received Diagnosed

: 18 Jul 2023 : 20 Jul 2023 Diagnostician : Don Baldridge

Test Package : FLEET (Additional Tests: PrtCount)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

E.C. PACE CO. 1811 HOLLINS RD. ROANOKE, VA US 24012

Contact: EDDIE SECO ESECO@ECPACE.COM

T: (276)266-5849 F: (540)343-6909

Contact/Location: EDDIE SECO - ECPROA