

PROBLEM SUMMARY

ROBIN B INGRAM Machine Id [ROBIN B INGRAM] 003 617985-3


Component


Starboard Main Engine


CHEVRON DELO 710 LE (250 GAL)


Sample Rating Trend DIRT 2017 Fee2018 Oct2018 Ju2013 Aud2020 Jun02021 Apz2022 Fee2023

COMPONENT CONDITION SUMMARY









RECOMMENDATION

We advise that you check for the source of the coolant leak. Check for low coolant level. We advise that you check the air filter, air induction system, and any areas where dirt may enter the component. We recommend an early resample to monitor this condition.

PROBLEMATIC TEST RESULTS								
Sample Status				ABNORMAL	ATTENTION	NORMAL		
Aluminum	ppm	ASTM D5185m	>15	<u>^</u> 6	<1	<1		
Lead	ppm	ASTM D5185m	>18	△ 38	21	10		
Copper	ppm	ASTM D5185m	>80	△ 38	13	16		
Silicon	ppm	ASTM D5185m	>20	27	11	8		
Sodium	ppm	ASTM D5185m	>75	<u> </u>	△ 76	37		
Potassium	ppm	ASTM D5185m	>20	<u> </u>	5	5		

Customer Id: INGPAD Sample No.: MW05901973 Lab Number: 05901973 Test Package: MAR 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Jonathan Hester +1 919-379-4092 x4092 jhester@wearcheckusa.com

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com

RECOMMENDED ACTIONS

Action	Status	Date	Done By	Description
Resample	MISSED	Jul 20 2023	?	We recommend an early resample to monitor this condition.
Check Dirt Access	MISSED	Jul 20 2023	?	We advise that you check the air filter, air induction system, and any areas where dirt may enter the component.
Check Glycol Access	MISSED	Jul 20 2023	?	We advise that you check for the source of the coolant leak.

HISTORICAL DIAGNOSIS

01 Jun 2023 Diag: Don Baldridge

COOLANT



No corrective action is recommended at this time. Resample at the next service interval to monitor. All component wear rates are normal. The high sodium (Na) level indicates the possible presence of salt water. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.



31 Mar 2023 Diag: Wes Davis

NORMAL



Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

view report

01 Mar 2023 Diag: Wes Davis

NORMAL



Resample at the next service interval to monitor. All component wear rates are normal. There is no indication of any contamination in the oil. The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.





OIL ANALYSIS REPORT

ROBIN B INGRAM [ROBIN B INGRAM] 003 617985-3

Starboard Main Engine

CHEVRON DELO 710 LE (250 GAL)

Sample Rating Trend



DIAGNOSIS

Recommendation

We advise that you check for the source of the coolant leak. Check for low coolant level. We advise that you check the air filter, air induction system, and any areas where dirt may enter the component. We recommend an early resample to monitor this condition.

Wear

Bearing and/or bushing wear is indicated.

Contamination

Sodium and/or potassium levels are high. Elemental levels of silicon (Si) and aluminum (Al) indicate alumina-silicate (coarse dirt) ingress.

▲ Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil.

Sample Date Client Info 01 Jun 2023 31 Mar 2023 32 Mar 244 37 September 37 September 37 September 37 September 37 September 37 September 38 Mar 34 Morrison 37 September 37 September 38 Mar 34 Morrison 31 Mar 2023 32 September 37 September 37 September 38 Morrison 32 Mar 34 Morrison 31 Mar 2023 32 Mar 34 Morrison 32 Mar 34 Morrison 31 Mar 2023 32 Mar 34 Morrison 32 Mar 34 Morrison 32 Mar 34 Morrison 32 Mar 34 Morrison 33 Mar 2021 34 Morrison			g2017 Feb20	18 Oct2018 Jul2019	Apr2020 Jun2021 Apr2022 F	eb2023	
Sample Date Client Info 01 Jun 2023 31 Mar 2023 32 Mar 244 37 September 37 September 37 September 37 September 37 September 37 September 38 Mar 34 Morrison 37 September 37 September 38 Mar 34 Morrison 31 Mar 2023 32 September 37 September 37 September 38 Morrison 32 Mar 34 Morrison 31 Mar 2023 32 Mar 34 Morrison 32 Mar 34 Morrison 31 Mar 2023 32 Mar 34 Morrison 32 Mar 34 Morrison 32 Mar 34 Morrison 32 Mar 34 Morrison 33 Mar 2021 34 Morrison	SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Machine Age hrs Client Info 52520 57848 57244 Oil Age hrs Client Info 0 57848 275 Oil Changed Client Info N/A NNOt Changed N/A Sample Status Image: Control of the property	Sample Number		Client Info		MW05901973	MW0027295	MW05875095
Oil Age hrs Client Info NA 57848 275 Oil Changed Client Info NA NA Not Changd NA Sample Status ABNORMAL ATTENTION NORMAL CONTAMINATION method limit/base current history1 history2 Fuel WC Method <-1.0 <-1.0 <-1.0 <-1.0 WEAR METALS method limit/base current history1 history2 Iron ppm ASTM D5185m >-75 25 17 18 Chromium ppm ASTM D5185m >-8 -1 -1 -1 Nickel ppm ASTM D5185m >-2 -1 0 0 ASTM D5185m >-2 -1 0 0 0 Alluminum ppm ASTM D5185m >-2 0 0 0 Alluminum ppm ASTM D5185m >-14 2 2 3 Vanadium	Sample Date		Client Info		01 Jun 2023	01 Jun 2023	31 Mar 2023
Contament Con	Machine Age	hrs	Client Info		52520	57848	57244
ABNORMAL ATTENTION NORMAL	Oil Age	hrs	Client Info		0	57848	275
CONTAMINATION	Oil Changed		Client Info		N/A	Not Changd	N/A
WEAR METALS	Sample Status				ABNORMAL	ATTENTION	NORMAL
WEAR METALS method limit/base current history1 history2 Iron ppm ASTM D5185m >75 25 17 18 Chromium ppm ASTM D5185m >8 <1 <1 <1 Nickel ppm ASTM D5185m >2 <1 0 0 Silver ppm ASTM D5185m >2 0 0 0 Aluminum ppm ASTM D5185m >15 6 <1 <1 Lead ppm ASTM D5185m >15 6 <1 <1 Copper ppm ASTM D5185m >14 2 2 3 Vanadium ppm ASTM D5185m >14 2 2 3 Vanadium ppm ASTM D5185m <1 0 <1 <1 Cadmium ppm ASTM D5185m <1 0 0 Barium ppm ASTM D5185m 58 54 44	CONTAMINATION		method	limit/base	current	history1	history2
Iron	Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Chromium ppm ASTM D5185m >8 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <td>WEAR METALS</td> <td></td> <td>method</td> <td>limit/base</td> <th>current</th> <td>history1</td> <td>history2</td>	WEAR METALS		method	limit/base	current	history1	history2
Nickel	Iron	ppm	ASTM D5185m	>75	25	17	18
Titanium	Chromium	ppm	ASTM D5185m	>8	<1	<1	<1
Silver	Nickel	ppm	ASTM D5185m	>2	<1	0	0
Aluminum ppm ASTM D5185m >15 ▲ 6 <1 <1 Lead ppm ASTM D5185m >18 ▲ 38 21 10 Copper ppm ASTM D5185m >80 ▲ 38 13 16 Tin ppm ASTM D5185m >14 2 2 3 Vanadium ppm ASTM D5185m 0 <1	Titanium	ppm	ASTM D5185m	>3	<1	0	0
Lead ppm ASTM D5185m >18 ▲ 38 21 10 Copper ppm ASTM D5185m >80 ▲ 38 13 16 Tin ppm ASTM D5185m >14 2 2 3 Vanadium ppm ASTM D5185m 0 <1 <1 <1 Cadmium ppm ASTM D5185m 58 54 44 Boron ppm ASTM D5185m 58 54 44 Barium ppm ASTM D5185m 0 0 0 Molybdenum ppm ASTM D5185m 46 44 48 Manganese ppm ASTM D5185m <1 <1 <1 <1 Magnesium ppm ASTM D5185m 3264 3394 3581 Phosphorus ppm ASTM D5185m 8 15 <19 Zinc ppm ASTM D5185m 20 2427 2669 2849 CONTAMINA	Silver	ppm	ASTM D5185m	>2	0	0	0
Copper ppm ASTM D5185m >80 ▲ 38 13 16 Tin ppm ASTM D5185m >14 2 2 3 Vanadium ppm ASTM D5185m 0 <1	Aluminum	ppm	ASTM D5185m	>15	<u>^</u> 6	<1	<1
Tin	Lead	ppm	ASTM D5185m	>18	4 38	21	10
Vanadium ppm ASTM D5185m 0 <1 <1 Cadmium ppm ASTM D5185m <1 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185m 58 54 44 Barium ppm ASTM D5185m 0 0 0 Molybdenum ppm ASTM D5185m 46 44 48 Manganese ppm ASTM D5185m 121 51 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 <1 </td <td>Copper</td> <td>ppm</td> <td>ASTM D5185m</td> <td>>80</td> <th>△ 38</th> <td>13</td> <td>16</td>	Copper	ppm	ASTM D5185m	>80	△ 38	13	16
Cadmium ppm ASTM D5185m <1 0 0 ADDITIVES method limit/base current history1 history2 Boron ppm ASTM D5185m 58 54 44 Barium ppm ASTM D5185m 0 0 0 Molybdenum ppm ASTM D5185m 46 44 48 Manganese ppm ASTM D5185m <1	Tin	ppm	ASTM D5185m	>14	2	2	3
ADDITIVES	Vanadium	ppm	ASTM D5185m		0	<1	<1
Boron	Cadmium	ppm	ASTM D5185m		<1	0	0
Barium ppm ASTM D5185m 0 0 0 Molybdenum ppm ASTM D5185m 46 44 48 Manganese ppm ASTM D5185m <1 <1 <1 Magnesium ppm ASTM D5185m 121 51 42 Calcium ppm ASTM D5185m 3264 3394 3581 Phosphorus ppm ASTM D5185m 8 15 19 Zinc ppm ASTM D5185m 10 24 6 7 Sulfur ppm ASTM D5185m 2427 2669 2849 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 27 11 8 Sodium ppm ASTM D5185m >20 16 5 5 Fluid ppm ASTM D5185m >20 16 5 5 Solium ppm ASTM D5185m	ADDITIVES		method	limit/base	current	history1	history2
Molybdenum ppm ASTM D5185m 46 44 48 Manganese ppm ASTM D5185m <1 <1 <1 Magnesium ppm ASTM D5185m 121 51 42 Calcium ppm ASTM D5185m 3264 3394 3581 Phosphorus ppm ASTM D5185m 8 15 19 Zinc ppm ASTM D5185m 10 24 6 7 Sulfur ppm ASTM D5185m 2427 2669 2849 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 27 11 8 Sodium ppm ASTM D5185m >20 16 5 5 Glycol % *ASTM D5185m >20 16 5 5 Glycol % *ASTM D5185m >20 16 5 5 INFRA-RED method	Boron	ppm	ASTM D5185m		58	54	44
Manganese ppm ASTM D5185m <1 <1 <1 Magnesium ppm ASTM D5185m 121 51 42 Calcium ppm ASTM D5185m 3264 3394 3581 Phosphorus ppm ASTM D5185m 8 15 19 Zinc ppm ASTM D5185m 10 24 6 7 Sulfur ppm ASTM D5185m 2427 2669 2849 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 27 11 8 Sodium ppm ASTM D5185m >20 16 5 5 Glycol % *ASTM D5185m >20 16 5 5 Glycol % *ASTM D5185m >20 16 5 5 Glycol % *ASTM D5185m >20 NEG NEG NEG INFRA-RED	Barium	ppm	ASTM D5185m		0	0	0
Magnesium ppm ASTM D5185m 121 51 42 Calcium ppm ASTM D5185m 3264 3394 3581 Phosphorus ppm ASTM D5185m 8 15 19 Zinc ppm ASTM D5185m 10 24 6 7 Sulfur ppm ASTM D5185m 2427 2669 2849 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 27 11 8 Sodium ppm ASTM D5185m >75 214 76 37 Potassium ppm ASTM D5185m >20 16 5 5 Glycol % *ASTM D5185m >20 16 5 5 Glycol % *ASTM D5185m >20 NEG NEG NEG INFRA-RED method limit/base current history1 history2 <	Molybdenum	ppm	ASTM D5185m		46	44	48
Calcium ppm ASTM D5185m 3264 3394 3581 Phosphorus ppm ASTM D5185m 8 15 19 Zinc ppm ASTM D5185m 10 24 6 7 Sulfur ppm ASTM D5185m 2427 2669 2849 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 27 11 8 Sodium ppm ASTM D5185m >75 214 76 37 Potassium ppm ASTM D5185m >20 16 5 5 Glycol % *ASTM D5185m >20 16 5 5 Glycol % *ASTM D5185m >20 NEG NEG NEG INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7624 >20 7.1 6.8 8.9	Manganese	ppm	ASTM D5185m		<1	<1	<1
Phosphorus ppm ASTM D5185m 8 15 19 Zinc ppm ASTM D5185m 10 24 6 7 Sulfur ppm ASTM D5185m 2427 2669 2849 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 27 11 8 Sodium ppm ASTM D5185m >75 214 76 37 Potassium ppm ASTM D5185m >20 16 5 5 Glycol % *ASTM D5185m >20 16 5 5 MEG NEG NEG NEG NEG INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 >3 0.4 0.3 0.7 Nitration Abs/.1mm *ASTM D7415 >30 15.8 15.6 17.4 FLUI	Magnesium	ppm	ASTM D5185m		121	51	42
Zinc ppm ASTM D5185m 10 24 6 7 Sulfur ppm ASTM D5185m 2427 2669 2849 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 27 11 8 Sodium ppm ASTM D5185m >75 214 76 37 Potassium ppm ASTM D5185m >20 16 5 5 Glycol % *ASTM D2982 NEG NEG NEG INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 >3 0.4 0.3 0.7 Nitration Abs/cm *ASTM D7624 >20 7.1 6.8 8.9 Sulfation Abs/.1mm *ASTM D7415 >30 15.8 15.6 17.4 FLUID DEGRADATION method limit/base current histor	Calcium	ppm	ASTM D5185m		3264	3394	3581
Sulfur ppm ASTM D5185m 2427 2669 2849 CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 27 11 8 Sodium ppm ASTM D5185m >75 214 76 37 Potassium ppm ASTM D5185m >20 16 5 5 Glycol % *ASTM D2982 NEG NEG NEG INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 >3 0.4 0.3 0.7 Nitration Abs/cm *ASTM D7624 >20 7.1 6.8 8.9 Sulfation Abs/.1mm *ASTM D7415 >30 15.8 15.6 17.4 FLUID DEGRADATION method limit/base current history1 history2 Oxidation Abs/.1mm *ASTM D7414 >25 6	Phosphorus	ppm	ASTM D5185m		8	15	19
CONTAMINANTS method limit/base current history1 history2 Silicon ppm ASTM D5185m >20 ▲ 27 11 8 Sodium ppm ASTM D5185m >75 ▲ 214 ▲ 76 37 Potassium ppm ASTM D5185m >20 ▲ 16 5 5 Glycol % *ASTM D2982 NEG NEG NEG INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 >3 0.4 0.3 0.7 Nitration Abs/cm *ASTM D7624 >20 7.1 6.8 8.9 Sulfation Abs/.1mm *ASTM D7415 >30 15.8 15.6 17.4 FLUID DEGRADATION method limit/base current history1 history2 Oxidation Abs/.1mm *ASTM D7414 >25 6.4 6.6 8.4	Zinc	ppm	ASTM D5185m	10	24	6	7
Silicon ppm ASTM D5185m >20 27 11 8 Sodium ppm ASTM D5185m >75 214 76 37 Potassium ppm ASTM D5185m >20 16 5 5 Glycol % *ASTM D2982 NEG NEG NEG INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 >3 0.4 0.3 0.7 Nitration Abs/cm *ASTM D7624 >20 7.1 6.8 8.9 Sulfation Abs/.1mm *ASTM D7415 >30 15.8 15.6 17.4 FLUID DEGRADATION method limit/base current history1 history2 Oxidation Abs/.1mm *ASTM D7414 >25 6.4 6.6 8.4	Sulfur	ppm	ASTM D5185m		2427	2669	2849
Sodium ppm ASTM D5185m >75 ▲ 214 ▲ 76 37 Potassium ppm ASTM D5185m >20 ▲ 16 5 5 Glycol % *ASTM D2982 NEG NEG NEG INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 >3 0.4 0.3 0.7 Nitration Abs/cm *ASTM D7624 >20 7.1 6.8 8.9 Sulfation Abs/.1mm *ASTM D7415 >30 15.8 15.6 17.4 FLUID DEGRADATION method limit/base current history1 history2 Oxidation Abs/.1mm *ASTM D7414 >25 6.4 6.6 8.4	CONTAMINANTS		method	limit/base	current	history1	history2
Potassium ppm ASTM D5185m >20 ▲ 16 5 5 Glycol % *ASTM D2982 NEG NEG NEG INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 >3 0.4 0.3 0.7 Nitration Abs/cm *ASTM D7624 >20 7.1 6.8 8.9 Sulfation Abs/.1mm *ASTM D7415 >30 15.8 15.6 17.4 FLUID DEGRADATION method limit/base current history1 history2 Oxidation Abs/.1mm *ASTM D7414 >25 6.4 6.6 8.4	Silicon	ppm	ASTM D5185m	>20	<u> </u>	11	8
NEG NEG	Sodium	ppm	ASTM D5185m	>75	<u> </u>	<u>^</u> 76	37
INFRA-RED method limit/base current history1 history2 Soot % % *ASTM D7844 >3 0.4 0.3 0.7 Nitration Abs/cm *ASTM D7624 >20 7.1 6.8 8.9 Sulfation Abs/.1mm *ASTM D7415 >30 15.8 15.6 17.4 FLUID DEGRADATION method limit/base current history1 history2 Oxidation Abs/.1mm *ASTM D7414 >25 6.4 6.6 8.4	Potassium	ppm	ASTM D5185m	>20	16	5	5
Soot % % *ASTM D7844 >3 0.4 0.3 0.7 Nitration Abs/cm *ASTM D7624 >20 7.1 6.8 8.9 Sulfation Abs/.1mm *ASTM D7415 >30 15.8 15.6 17.4 FLUID DEGRADATION method limit/base current history1 history2 Oxidation Abs/.1mm *ASTM D7414 >25 6.4 6.6 8.4	Glycol	%	*ASTM D2982		NEG	NEG	NEG
Nitration Abs/cm *ASTM D7624 >20 7.1 6.8 8.9 Sulfation Abs/.1mm *ASTM D7415 >30 15.8 15.6 17.4 FLUID DEGRADATION method limit/base current history1 history2 Oxidation Abs/.1mm *ASTM D7414 >25 6.4 6.6 8.4	INFRA-RED		method	limit/base	current	history1	history2
Nitration Abs/cm *ASTM D7624 > 20 7.1 6.8 8.9 Sulfation Abs/.1mm *ASTM D7415 > 30 15.8 15.6 17.4 FLUID DEGRADATION method limit/base current history1 history2 Oxidation Abs/.1mm *ASTM D7414 > 25 6.4 6.6 8.4	Soot %	%	*ASTM D7844	>3	0.4	0.3	0.7
Sulfation Abs/.1mm *ASTM D7415 >30 15.8 15.6 17.4 FLUID DEGRADATION method limit/base current history1 history2 Oxidation Abs/.1mm *ASTM D7414 >25 6.4 6.6 8.4	Nitration	Abs/cm	*ASTM D7624	>20	7.1		8.9
Oxidation Abs/.1mm *ASTM D7414 >25 6.4 6.6 8.4	Sulfation						
	FLUID DEGRADA	TION	method	limit/base	current	history1	history2
	Oxidation	Abs/.1mm	*ASTM D7414	>25	6.4	6.6	8.4
	Base Number (BN)	mg KOH/g		9.2	10.15	10.60	9.55



OIL ANALYSIS REPORT

