




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**TADANO 1600-56T**  
 Component  
**Hydraulic System**  
 Fluid  
**SHELL TELLUS T32 (250 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

The system cleanliness is acceptable for your target ISO 4406 cleanliness code. The system and fluid cleanliness is acceptable.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2
Sample Number	Client Info	<b>WC0836615</b>	---	---
Sample Date	Client Info	<b>18 Jul 2023</b>	---	---
Machine Age	hrs Client Info	<b>44</b>	---	---
Oil Age	hrs Client Info	<b>0</b>	---	---
Oil Changed	Client Info	<b>Filtered</b>	---	---
Sample Status		<b>NORMAL</b>	---	---

## WEAR METALS

method	limit/base	current	history1	history2
Iron ppm ASTM D5185m	>20	<b>&lt;1</b>	---	---
Chromium ppm ASTM D5185m	>20	<b>0</b>	---	---
Nickel ppm ASTM D5185m	>20	<b>0</b>	---	---
Titanium ppm ASTM D5185m		<b>0</b>	---	---
Silver ppm ASTM D5185m		<b>&lt;1</b>	---	---
Aluminum ppm ASTM D5185m	>20	<b>0</b>	---	---
Lead ppm ASTM D5185m	>20	<b>&lt;1</b>	---	---
Copper ppm ASTM D5185m	>20	<b>&lt;1</b>	---	---
Tin ppm ASTM D5185m	>20	<b>0</b>	---	---
Vanadium ppm ASTM D5185m		<b>0</b>	---	---
Cadmium ppm ASTM D5185m		<b>0</b>	---	---

## ADDITIVES

method	limit/base	current	history1	history2
Boron ppm ASTM D5185m		<b>0</b>	---	---
Barium ppm ASTM D5185m		<b>1</b>	---	---
Molybdenum ppm ASTM D5185m		<b>0</b>	---	---
Manganese ppm ASTM D5185m		<b>0</b>	---	---
Magnesium ppm ASTM D5185m		<b>51</b>	---	---
Calcium ppm ASTM D5185m	48	<b>18</b>	---	---
Phosphorus ppm ASTM D5185m	337	<b>326</b>	---	---
Zinc ppm ASTM D5185m	426	<b>293</b>	---	---
Sulfur ppm ASTM D5185m	2280	<b>844</b>	---	---

## CONTAMINANTS

method	limit/base	current	history1	history2
Silicon ppm ASTM D5185m	>15	<b>&lt;1</b>	---	---
Sodium ppm ASTM D5185m		<b>0</b>	---	---
Potassium ppm ASTM D5185m	>20	<b>2</b>	---	---

## FLUID CLEANLINESS





method	limit/base	current	history1	history2
Particles >4µm ASTM D7647	>2500	<b>567</b>	---	---
Particles >6µm ASTM D7647	>320	<b>98</b>	---	---
Particles >14µm ASTM D7647	>80	<b>9</b>	---	---
Particles >21µm ASTM D7647	>20	<b>3</b>	---	---
Particles >38µm ASTM D7647	>4	<b>0</b>	---	---
Particles >71µm ASTM D7647	>3	<b>0</b>	---	---
Oil Cleanliness ISO 4406 (c)	>18/15/13	<b>16/14/10</b>	---	---

## FLUID DEGRADATION

method	limit/base	current	history1	history2
Acid Number (AN) mg KOH/g ASTM D8045	.6	<b>0.38</b>	---	---



# OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	---	---
Yellow Metal	scalar	*Visual	NONE	NONE	---	---
Precipitate	scalar	*Visual	NONE	NONE	---	---
Silt	scalar	*Visual	NONE	NONE	---	---
Debris	scalar	*Visual	NONE	NONE	---	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---	---
Appearance	scalar	*Visual	NORML	NORML	---	---
Odor	scalar	*Visual	NORML	NORML	---	---
Emulsified Water	scalar	*Visual	>0.05	NEG	---	---
Free Water	scalar	*Visual		NEG	---	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 40°C	cSt	ASTM D445	32.21	<b>32.5</b>	---	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------

Color		no image	no image
Bottom		no image	no image

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0836615      **Received** : 20 Jul 2023  
**Lab Number** : 05903200      **Diagnosed** : 21 Jul 2023  
**Unique Number** : 10564556      **Diagnostician** : Wes Davis  
**Test Package** : IND 2

**TADANO MANTIS CORPORATION**  
 2680 S FRONT ST  
 RICHLANDS, VA  
 US 24641  
 Contact: CHRIS RASNAKE  
 chris.rasnake@tadano.com  
 T:  
 F: (615)370-5670

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)