


OIL ANALYSIS REPORT



OKLAHOMA/102/EG - DOZER 36.34L [OKLAHOMA^102^EG - DOZER]

Left Final Drive

MOBIL DELVAC 1350 (--- GAL)



Sample Rating Trend



Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: 9043 hrs)

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

Confirm oil type. The condition of the oil is acceptable for the time in service.

(GAL)		fay2016 Jan2	017 Nov2017 Nov2018	Feb 2020 May 2021 Oct 2021 Aug	2022 Jul202:	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0746893	WC0603264	WC0649343
Sample Date		Client Info		15 Jul 2023	17 Jan 2023	26 Aug 2022
Machine Age	hrs	Client Info		9043	8131	7832
Oil Age	hrs	Client Info		6969	6969	6969
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>800	48	40	39
Chromium	ppm	ASTM D5185m	>10	2	2	1
Nickel	ppm	ASTM D5185m	>5	0	0	0
Titanium	ppm	ASTM D5185m	>15	0	<1	<1
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>75	2	2	3
Lead	ppm	ASTM D5185m	>10	0	0	<1
Copper	ppm	ASTM D5185m	>75	0	<1	<1
Tin	ppm	ASTM D5185m	>8	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		2	3	5
Barium	ppm	ASTM D5185m		0	2	0
Molybdenum	ppm	ASTM D5185m		2	2	2
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		17	10	10
Calcium	ppm	ASTM D5185m		1639	993	1147
Phosphorus	ppm	ASTM D5185m		768	592	659
Zinc	ppm	ASTM D5185m		682	415	457
Sulfur	ppm	ASTM D5185m		6098	4512	4124
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>400	24	20	23
Sodium	ppm	ASTM D5185m		0	2	0
Potassium	ppm	ASTM D5185m	>20	2	<1	3
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	LIGHT	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	TIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	208	158	153	154



OIL ANALYSIS REPORT



SAMPLE IMAGES	method	limit/base	current	history1	history2
Color			no image	no image	回译集字 WC0649343
Bottom			no image	no image	

GRAPHS Ferrous Alloys 50 20 15 Non-ferrous Metals ppm Viscosity @ 40°C 260 240 230 220 (210 210 ±3 200 190 180 170 160 150





Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10565371 Test Package : CONST

: WC0746893 : 05904015

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 20 Jul 2023 Diagnosed : 24 Jul 2023

Diagnostician : Don Baldridge

SHERWOOD CONSTRUCTION CO INC 3219 WEST MAY ST

WICHITA, KS US 67213 Contact: DOUG KING doug.king@sherwood.net T: (316)617-3161

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: x: