




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
Speedway
 Machine Id
[Speedway] Oil - Starboard Main Engine
 Component
Starboard Main Engine
 Fluid
SAE 40W (150 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: Jd Ridout)

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0735481	WC0735380	WC0735685
Sample Date	Client Info		10 Jul 2023	10 Jun 2023	10 May 2023
Machine Age	hrs	Client Info	16357	15986	15437
Oil Age	hrs	Client Info	15200	14829	14283
Oil Changed	Client Info		Not Changed	Oil Added	Not Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>4.0	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >75	16	14	15
Chromium	ppm	ASTM D5185m >8	1	1	<1
Nickel	ppm	ASTM D5185m >2	<1	0	0
Titanium	ppm	ASTM D5185m >3	0	<1	0
Silver	ppm	ASTM D5185m >2	0	0	0
Aluminum	ppm	ASTM D5185m >15	4	3	<1
Lead	ppm	ASTM D5185m >18	7	6	6
Copper	ppm	ASTM D5185m >80	24	19	20
Tin	ppm	ASTM D5185m >14	9	9	8
Vanadium	ppm	ASTM D5185m	0	<1	0
Cadmium	ppm	ASTM D5185m	0	<1	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	7	6	7
Barium	ppm	ASTM D5185m	2	0	0
Molybdenum	ppm	ASTM D5185m	31	31	31
Manganese	ppm	ASTM D5185m	<1	<1	0
Magnesium	ppm	ASTM D5185m	25	22	21
Calcium	ppm	ASTM D5185m	3330	3417	3164
Phosphorus	ppm	ASTM D5185m	48	47	47
Zinc	ppm	ASTM D5185m	27	16	9
Sulfur	ppm	ASTM D5185m	4251	4952	4176

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >20	4	4	3
Sodium	ppm	ASTM D5185m >75	0	1	1
Potassium	ppm	ASTM D5185m >20	1	<1	0

INFRA-RED




	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	0.8	0.7	0.7
Nitration	Abs/cm	*ASTM D7624 >20	10.4	9.9	10.0
Sulfation	Abs/.1mm	*ASTM D7415 >30	19.1	19.5	18.8

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	13.8	14.8	13.2
Base Number (BN)	mg KOH/g	ASTM D2896	8.50	8.91	9.20







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.5	14.9	14.9	14.8

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0735481 **Received** : 21 Jul 2023
Lab Number : **05904531** **Diagnosed** : 01 Aug 2023
Unique Number : 10565887 **Diagnostician** : Doug Bogart
Test Package : IND 2 (Additional Tests: KF)

MARATHON PETROLEUM CO.
 101 12TH ST
 CATLETTSBURG, KY
 US 41169
 Contact: CORY GUMBERT
 cagumbert@marathonpetroleum.com
 T: (606)585-3950
 F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)