

OIL ANALYSIS REPORT

Area [1773308] SW05 (S/N 1661383)

Gearbox

MOBIL SHC 632 (2 GAL)

.....

Sample Rating Trend



Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: Monthly oil change and sample)

All component wear rates are normal.

Contamination

There is no indication of any contamination in the

Fluid Condition


The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		w2020 Sep20			Feb 2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0834249	WC0807601	WC0794312
Sample Date		Client Info		10 Jul 2023	17 May 2023	20 Apr 2023
Machine Age	hrs	Client Info		7977	9026	8200
Oil Age	hrs	Client Info		7977	826	472
Oil Changed		Client Info		Changed	Changed	N/A
Sample Status				NORMAL	ABNORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	<1	1	<1
Chromium	ppm	ASTM D5185m	>15	0	0	0
Nickel	ppm	ASTM D5185m	>15	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	3	2	0
Lead	ppm	ASTM D5185m	>100	0	0	0
Copper	ppm	ASTM D5185m	>200	<1	3	<1
Tin	ppm	ASTM D5185m	>25	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		<1	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m		<1	<1	<1
Calcium	ppm	ASTM D5185m		7	12	<1
Phosphorus	ppm	ASTM D5185m		539	446	464
Zinc	ppm	ASTM D5185m		8	13	5
Sulfur	ppm	ASTM D5185m		151	2	33
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	7	10	7
Sodium	ppm	ASTM D5185m		0	<1	0
Potassium	ppm	ASTM D5185m	>20	0	0	<1
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.47	0.49	0.49
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	▲ MODER	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
0 44 00\ D						




300


OIL ANALYSIS REPORT





FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	325.8	357	354	355
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color						
Bottom						2

Ferrous Alloys 10 шии













Laboratory Sample No. Lab Number **Unique Number** Test Package : IND 2

: WC0834249 : 05905637 : 10566993

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 24 Jul 2023 : 25 Jul 2023 Diagnosed Diagnostician : Don Baldridge

LEPRINO FOODS-FORT MORGAN 2400 EAST BEAVER AVE

FORT MORGAN, CO US 80701

Contact: KEITH SCHULTE kschulte@leprinofoods.com

T: (970)542-4247 F: (970)542-4241

Certificate L2367 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: LEPFOR [WUSCAR] 05905637 (Generated: 07/25/2023 19:44:09) Rev: 1