


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id MB10427

Component

Hydraulic System

PHILLIPS 66 Powerflow NZ AW46 (--- QTS)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the

Fluid Condition

The condition of the oil is acceptable for the time in service.

			Aug2022	Jul2023		
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0799367	WC0719681	
Sample Date		Client Info		31 Jul 2023	08 Aug 2022	
Machine Age	hrs	Client Info		0	0	
Oil Age	hrs	Client Info		0	0	
Oil Changed	1113	Client Info		N/A	N/A	
Sample Status		Oliciti IIIIO		NORMAL	NORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	nnm	ASTM D5185m	>20	5	5	
Chromium	ppm	ASTM D5185m	>20	6	<1	
	ppm			_		
Nickel	ppm	ASTM D5185m	>20	<1	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m	00	0	0	
Aluminum	ppm	ASTM D5185m	>20	0	<1	
Lead	ppm	ASTM D5185m	>20	<1	<1	
Copper	ppm	ASTM D5185m	>20	28	14	
Tin	ppm	ASTM D5185m	>20	0	<1	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m		1	1	
Molybdenum	ppm	ASTM D5185m		0	<1	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m		<1	<1	
Calcium	ppm	ASTM D5185m		21	79	
Phosphorus	ppm	ASTM D5185m		246	390	
Zinc	ppm	ASTM D5185m		237	533	
Sulfur	ppm	ASTM D5185m		1103	2792	
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	1	<1	
Sodium	ppm	ASTM D5185m		0	<1	
Potassium	ppm	ASTM D5185m	>20	0	1	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	VLITE	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
FLUID PROPER		method	limit/base		history1	history2
TEOID I NOI EN	HLO	metriou	- IIIIIVDase	- Guirein	Thistory I	— HISTORYZ

Visc @ 40°C


cSt

ASTM D445 46

45.4




OIL ANALYSIS REPORT







GRAPHS



Non-ferrous Metals









Certificate L2367

Laboratory Sample No. Lab Number

Unique Number : 10602547 Test Package : IND 1

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : WC0799367 : 05922600

Received : 11 Aug 2023 Diagnosed

: 14 Aug 2023 Diagnostician : Don Baldridge

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

SUMIRIKO TENNESSEE INC

150 HESTER LN TAZEWELL, TN US 37879

Contact: JEREMY COLLINS jcollins@us.sumiriko.com

T: (423)626-8805 F: (423)626-2065