

## **PROBLEM SUMMARY**

# NOT GIVEN WC0806774 (S/N NO INFO ON SIF/BOTTLE)

Gearbox Fluid NOT GIVEN (--- GAL)

# Sample Rating Trend WEAR





#### RECOMMENDATION

We recommend you service the filters on this component. Resample at the next service interval to monitor.

#### PROBLEMATIC TEST RESULTS

Sample Status				ABNORMAL	 
Aluminum	ppm	ASTM D5185m	>25	<u> </u>	 
Particles >4µm		ASTM D7647	>20000	<b>A</b> 173551	 
Particles >6µm		ASTM D7647	>5000	<u> </u>	 
Particles >14µm		ASTM D7647	>640	🔺 1661	 
Particles >21µm		ASTM D7647	>160	<u> </u>	 
Oil Cleanliness		ISO 4406 (c)	>21/19/16	<u> </u>	 

Customer Id: TALCLA Sample No.: WC0806774 Lab Number: 05922842 Test Package: IND 2



To manage this report scan the QR code

*To discuss the diagnosis or test data:* Doug Bogart +1 (800)237-1369 x4016 <u>dougb@wearcheckusa.com</u>

To change component or sample information: Customer Service +1 1-800-237-1369 customerservice@wearcheck.com

RECOMMENDED ACTIONS						
Action	Status	Date	Done By	Description		
Change Filter			?	We recommend you service the filters on this component.		

HISTORICAL DIAGNOSIS



### **OIL ANALYSIS REPORT**

Sample Rating Trend

WEAR

#### Not GIVEN WC0806774 (S/N NO INFO ON SIF/BOTTLE) Component Gearbox

Fluid

#### NOT GIVEN (--- GAL)

# DIAGNOSIS

Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

#### 🔺 Wear

The aluminum level is abnormal. All other component wear rates are normal.

#### Contamination

There is a high amount of particulates present in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0806774		
Sample Date		Client Info		08 Aug 2023		
Machine Age	days	Client Info		540		
Oil Age	days	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	66		
Chromium	ppm	ASTM D5185m	>15	<1		
Nickel	ppm	ASTM D5185m	>15	0		
Titanium	ppm	ASTM D5185m		16		
Silver	ppm	ASTM D5185m		0		
Aluminum	maa	ASTM D5185m	>25	<b>4</b> 3		
Lead	ppm	ASTM D5185m	>100	0		
Copper	nnm	ASTM D5185m	>200	د د1		
Tin	nom	ASTM D5185m	>25	0		
Vanadium	nnm	ASTM D5185m	20	۰ ۲1		
Cadmium	ppm	ASTM D5185m		0		
	PP	mothod	limit/baco	ourropt	history1	history?
ADDITIVES			IIIIIVDase		TIIStory I	Thistoryz
Boron	ppm	ACTM DE105m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		U		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		2		
Calcium	ppm	ASTM D5185m		205		
Phosphorus	ppm	ASTM D5185m		549		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		736		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	17		
Sodium	ppm	ASTM D5185m		22		
Potassium	ppm	ASTM D5185m	>20	2		
Water	%	ASTM D6304	>0.2	0.011		
ppm Water	ppm	ASTM D6304	>2000	110.5		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>20000	<b>A</b> 173551		
Particles >6µm		ASTM D7647	>5000	<b>4</b> 91973		
Particles >14µm		ASTM D7647	>640	🔺 1661		
Particles >21µm		ASTM D7647	>160	<u> </u>		
Particles >38µm		ASTM D7647	>40	3		
Particles >71µm		ASTM D7647	>10	1		
Oil Cleanliness		ISO 4406 (c)	>21/19/16	<b>25/24/18</b>		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.34		



# **OIL ANALYSIS REPORT**



Contact/Location: KEN TERRY - TALCLA