


# **OIL ANALYSIS REPORT**

Ewing Hauling PETERBILT 2600

Component

Diesel Engine

GIBRALTAR 15W/40 SUPER S-3 LX (11)





# Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

# Contamination

There is no indication of any contamination in the


# **Fluid Condition**

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

				Aug2023		
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0830847		
Sample Date		Client Info		03 Aug 2023		
Machine Age	hrs	Client Info		9738		
Oil Age	hrs	Client Info		150		
Oil Changed		Client Info		Filtered		
Sample Status				NORMAL		
CONTAMINATION	J	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Glycol		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>110	14		
Chromium	ppm	ASTM D5185m	>4	0		
Nickel	ppm	ASTM D5185m	>2	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m	>2	<1		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>45	<1		
Copper	ppm	ASTM D5185m	>85	<1		
Tin	ppm	ASTM D5185m	>4	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		14		
Barium	ppm	ASTM D5185m		2		
Molybdenum	ppm	ASTM D5185m	660	72		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m	1000	768		
Calcium	ppm	ASTM D5185m	1050	1418		
Phosphorus	ppm	ASTM D5185m	1150	1076		
Zinc	ppm	ASTM D5185m	1270	1258		
Sulfur	ppm	ASTM D5185m		3695		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>30	3		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	6		
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	0.4		
Nitration	Abs/cm	*ASTM D7624	>20	7.4		
Sulfation	Abs/.1mm	*ASTM D7415	>30	18.5		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
FLUID DEGRADA Oxidation	TION Abs/.1mm	method *ASTM D7414	limit/base	current	history1	history2




# **OIL ANALYSIS REPORT**





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
<b>Emulsified Water</b>	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPER	TIES	method	limit/base	current	history1	history2

I LOID I NOI LI	THES	memou			HISTOLAL	HISTOLYZ
Visc @ 100°C	cSt	ASTM D445	15.5	14.1		

# Ferrous Alloys











Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10603157

: WC0830847 : 05923210 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received Diagnosed

: 14 Aug 2023 : 15 Aug 2023 Diagnostician : Don Baldridge

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

CEvans@interstatewaste.com

Report Id: INTEWI [WUSCAR] 05923210 (Generated: 08/15/2023 10:40:27) Rev: 1

**INTERSTATE WASTE-EWING** 

432 STOKES AVENUE

EWING TOWNSHIP, NJ

Contact: Carlos Evans

US 08638

T:

F: