


OIL ANALYSIS REPORT

OKLAHOMA/102
Machine Id
22.69L [OKLAHOMA^102]

Component
Main Hoist

MOBIL MOBILUBE HD PLUS 75W90 (--- GAL)





DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil


Fluid Condition

The condition of the oil is acceptable for the time in service.

AL)			May2022	Aug2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0833994	WC0662460	
Sample Date		Client Info		07 Aug 2023	13 May 2022	
Machine Age	hrs	Client Info		1744	1070	
Oil Age	hrs	Client Info		465	1070	
Oil Changed		Client Info		N/A	Changed	
Sample Status				NORMAL	NORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>300	13	92	
Chromium	ppm	ASTM D5185m	>5	<1	2	
Nickel	ppm	ASTM D5185m	>4	0	0	
Titanium	ppm	ASTM D5185m		<1	<1	
Silver	ppm	ASTM D5185m		0	<1	
Aluminum	ppm	ASTM D5185m	>10	1	8	
Lead	ppm	ASTM D5185m	>120	<1	0	
Copper	ppm	ASTM D5185m	>200	2	3	
Tin	ppm	ASTM D5185m	>15	0	<1	
Vanadium	ppm	ASTM D5185m		0	<1	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		90	8	
Barium	ppm	ASTM D5185m		5	5	
Molybdenum	ppm	ASTM D5185m		1	33	
Manganese	ppm	ASTM D5185m		<1	3	
Magnesium	ppm	ASTM D5185m		1112	5008	
Calcium	ppm	ASTM D5185m		65	61	
Phosphorus	ppm	ASTM D5185m		986	940	
Zinc	ppm	ASTM D5185m		349	730	
Sulfur	ppm	ASTM D5185m		11740	4514	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>75	12	63	
Sodium	ppm	ASTM D5185m		0	5	
Potassium	ppm	ASTM D5185m	>20	1	0	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	MODER	
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
FLUID PROPERT	TES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	85	106	106	





OIL ANALYSIS REPORT




SAMPLE IM	AGES	method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image

GRAPHS











Certificate L2367

Laboratory Sample No. Lab Number

Unique Number : 10603711 Test Package : CONST

: WC0833994 : 05923764

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 14 Aug 2023 Diagnosed : 15 Aug 2023 Diagnostician : Don Baldridge

SHERWOOD CONSTRUCTION CO INC

3219 WEST MAY ST WICHITA, KS US 67213

Contact: DALE CASINO dale.casino@sherwood.net

T:

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: SHEWIC [WUSCAR] 05923764 (Generated: 08/15/2023 14:29:10) Rev: 1

Submitted By: BOBBY JONES

F: