

OIL ANALYSIS REPORT

Sample Rating Trend



KAESER MR-AIRC-06 (S/N 1502)

Component

Compressor

ULTRACHEM OMNILUBE 32/46 (--- Oz)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

v2015 Dec2017 Ju2018 Ju2019 Feb2020 Sep2020 Nev2021 Apr2023						
SAMPLE INFORM	//ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0799712	WC0799705	WC0791929
Sample Date		Client Info		07 Aug 2023	10 Jul 2023	13 Jun 2023
Machine Age	hrs	Client Info		59438	59438	59436
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	N/A	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	<1	0
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm			1	1	<1
Tin	ppm		>10	0	0	0
Vanadium	ppm	ASTM D5185m	710	0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	1	0	0	0
Barium	ppm	ASTM D5185m	0.3	0	0	5
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m	0	0	0	6
Calcium	ppm	ASTM D5185m	0.5	0	<1	8
Phosphorus		ASTM D5185m	536	310	327	354
Zinc	ppm	ASTM D5185m	0.2	43	47	83
Sulfur	ppm		649		620	
	ppm	ASTM D5185m		490		558
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	0
Sodium	ppm	ASTM D5185m		1	<1	0
Potassium	ppm	ASTM D5185m	>20	0	<1	<1
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647	>40000	643	7510	6058
Particles >6µm		ASTM D7647	>5000	140	2179	2098
Particles >14µm		ASTM D7647	>640	9	89	106
Particles >21µm		ASTM D7647	>160	3	19	17
Particles >38µm		ASTM D7647	>40	0	1	0
Particles >71µm		ASTM D7647	>10	0	1	0
Oil Cleanliness		ISO 4406 (c)	>22/19/16	17/14/10	20/18/14	20/18/14
FLUID DEGRADA	ATION _	method	limit/base	current	history1	history2

Acid Number (AN) mg KOH/g ASTM D8045 0.337

0.50

0.54

0.53



OIL ANALYSIS REPORT







Certificate L2367

Laboratory Sample No.

Lab Number **Unique Number**

Test Package : IND 2 (Additional Tests: PrtCount)

(0.0b) \$5

35

: WC0799712 : 05924199

: 10604146

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 14 Aug 2023 Diagnosed

: 15 Aug 2023 : Don Baldridge Diagnostician

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Viscosity @ 40°C

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. **BURKE CORPORATION.**

1516 SOUTH D AVE NEVADA, IA US 50201

Contact: EDWARDO COBIO

JECOBIO@BURKECORP.COM T:

F: (515)382-3955

Acid Number

Number (mg) Acid O'O