



PROBLEM SUMMARY

Area AIRLUBE 228 Machine Id ELGI MRAL160131 - MARTIN MARIETTA Component Compressor



COMPONENT CONDITION SUMMARY



RECOMMENDATION

Recommend drain oil if not already done and flush with cleaner before refilling with oil.

PROE	LEMATIC TEST RESULTS

Sample Status			SEVERE	 	
Acid Number (AN)	mg KOH/g	ASTM D8045	0.463	e 5.43	
Visc @ 40°C	cSt	ASTM D445	47.9	A 72.5	

Customer Id: UCCISSAC Sample No.: UCH05924912 Lab Number: 05924912 Test Package: IND 2



To manage this report scan the QR code

To discuss the diagnosis or test data: Doug Bogart +1 (800)237-1369 x4016 <u>dougb@wearcheckusa.com</u>

To change component or sample information: Customer Service +1 1-800-237-1369 <u>customerservice@wearcheck.com</u>

RECOMMENDED	RECOMMENDED ACTIONS					
Action	Status	Date	Done By	Description		
Change Fluid			?	Recommend drain oil if not already done and flush with cleaner before refilling with oil.		
Flush System			?	Recommend drain oil if not already done and flush with cleaner before refilling with oil.		

HISTORICAL DIAGNOSIS



OIL ANALYSIS REPORT

Area AIRLUBE 228 Machine Id ELGI MRAL160131 - MARTIN MARIETTA Component

Compressor

DIAGNOSIS

Recommendation

Recommend drain oil if not already done and flush with cleaner before refilling with oil.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is above the recommended limit. The oil viscosity is higher than normal. TAN level indicates possible presence of varnish.

				Aug2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH05924912		
Sample Date		Client Info		10 Aug 2023		
Machine Age	hrs	Client Info		26401		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				SEVERE		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	3		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	<1		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	1.5	0		
Barium	ppm	ASTM D5185m	0	0		
Molybdenum	ppm	ASTM D5185m	0	0		
Manganese	ppm	ASTM D5185m	0.3	0		
Magnesium	ppm	ASTM D5185m	0	<1		
Calcium	ppm	ASTM D5185m	0	0		
Phosphorus	ppm	ASTM D5185m	406	6		
Zinc	ppm	ASTM D5185m	0	0		
Sulfur	ppm	ASTM D5185m	1283	0		
CONTAMINANTS	6	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	<1		
FLUID DEGRAD	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.463	• 5.43		
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.1	NEG		
Free Water	scalar	*Visual		NEG		
-02.08) Pov: 1			Con	taat/l agation: D/		LICCISCA

Sample Rating Trend



Contact/Location: BARRY FRKOVICH - UCCISSAC





 \mathbf{X}



OIL ANALYSIS REPORT

FLUID PROPERTIES





Contact/Location: BARRY FRKOVICH - UCCISSAC