




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id
ELMCO S AERATOR
 Component
Gearbox
 Fluid
ROYAL PURPLE SYNERGY 90/220 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		RP0020987	RP187358	---
Sample Date	Client Info		01 Aug 2023	30 Nov 2016	---
Machine Age	hrs	Client Info	53116	0	---
Oil Age	hrs	Client Info	0	0	---
Oil Changed	Client Info		Not Changed	N/A	---
Sample Status			NORMAL	NORMAL	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >200	120	71	---
Chromium	ppm	ASTM D5185m >15	<1	<1	---
Nickel	ppm	ASTM D5185m >15	0	<1	---
Titanium	ppm	ASTM D5185m	0	0	---
Silver	ppm	ASTM D5185m	0	0	---
Aluminum	ppm	ASTM D5185m >25	0	<1	---
Lead	ppm	ASTM D5185m >100	0	2	---
Copper	ppm	ASTM D5185m >200	<1	<1	---
Tin	ppm	ASTM D5185m >25	0	0	---
Antimony	ppm	ASTM D5185m >5	---	0	---
Vanadium	ppm	ASTM D5185m	<1	0	---
Cadmium	ppm	ASTM D5185m	<1	<1	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	57	43	---
Barium	ppm	ASTM D5185m	0	0	---
Molybdenum	ppm	ASTM D5185m	<1	0	---
Manganese	ppm	ASTM D5185m	2	<1	---
Magnesium	ppm	ASTM D5185m	3	1	---
Calcium	ppm	ASTM D5185m	41	36	---
Phosphorus	ppm	ASTM D5185m 370	794	714	---
Zinc	ppm	ASTM D5185m	5	10	---




CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >50	2	3	---
Sodium	ppm	ASTM D5185m	12	10	---
Potassium	ppm	ASTM D5185m >20	3	0	---
Water	%	ASTM D6304 >0.2	0.035	0.032	---
ppm Water	ppm	ASTM D6304 >2000	359.6	320	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045 1.33	1.60	1.39	---


OIL ANALYSIS REPORT







VISUAL	method	limit/base	current	history1	history2	
White Metal	scalar	*Visual	NONE	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	NONE	---
Debris	scalar	*Visual	NONE	LIGHT	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	---
Free Water	scalar	*Visual		NEG	NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 40°C	cSt	ASTM D445	216.1	211	210.6	---

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : RP0020987 **Received** : 16 Aug 2023
Lab Number : **05926180** **Diagnosed** : 17 Aug 2023
Unique Number : 10606127 **Diagnostician** : Don Baldrige
Test Package : IND 2

VISION INDUSTRIAL SALES
 132 SOUTH MOUNT VERNON DR
 IOWA CITY, IA
 US 52245

Contact: LEESA ELSEMAN
 vision@mchsi.com; jon.fazenbaker@wearcheck.com
 T: (319)341-5823
 F: (319)341-7867

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)