

OIL ANALYSIS REPORT

Sample Rating Trend


NORMAL



Grand Blanc CAT 4 GBLM04BE

Biogas Engine

CHEVRON HDAX 6500 LFG GAS ENGINE OIL (--- GAL)





GAS ENGINE OIL (GAL)	p2022 Oct20	22 Dec2022 Jan2023	Feb2023 Apr2023 May2023	lun2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number Sample Date Machine Age	hrs	Client Info Client Info Client Info		WC0825004 14 Aug 2023 63477	WC0824962 07 Aug 2023 63305	WC0825022 19 Jul 2023 62855
Oil Age	hrs	Client Info		394	226	628
Oil Changed		Client Info		Not Changd	Changed	Not Changd
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATIO	N	method	limit/base	current	history1	history2
Fuel		WC Method	>4.0	<1.0	<1.0	<1.0
Glycol		WC Method		NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>15	2	2	5
Chromium	ppm	ASTM D5185m	>4	0	0	<1
Nickel	ppm	ASTM D5185m	>2	0	0	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m	>5	0	0	0
Aluminum	ppm	ASTM D5185m		1	2	2
Lead	ppm	ASTM D5185m	>9	2	2	5
Copper	ppm	ASTM D5185m	>14	2	1	2
Tin	ppm	ASTM D5185m	>4	2	1	3
Vanadium	ppm	ASTM D5185m		<1	<1	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	2
Barium	ppm	ASTM D5185m		0	0	2
Molybdenum	ppm	ASTM D5185m		2	2	3
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m		11	11	13
Calcium	ppm	ASTM D5185m		1879	1961	1949
Phosphorus	ppm	ASTM D5185m		271	293	285
Zinc	ppm	ASTM D5185m		323	336	364
Sulfur	ppm	ASTM D5185m		3058	3069	3269
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>181	103	80	154
Sodium	ppm	ASTM D5185m		1	<1	0
Potassium	ppm	ASTM D5185m	>20	<1	0	1
INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844		0	0	0.1
A 124 - 12	A.L. /	******	00			0.1

Soot %	%	*ASTM D7844		0	0	0.1
Nitration	Abs/cm	*ASTM D7624	>20	5.7	5.7	6.1
Sulfation	Abs/.1mm	*ASTM D7415	>30	19.9	18.7	21.5
FLUID DEGRADA		method	limit/base	current	history1	history2
		mounou	initia baob	ourront	motory	motoryz
Oxidation	Abs/.1mm			11.9	10.5	13.3
		*ASTM D7414	>25		· · · · ·	

Recommendation

Resample at the next service interval to monitor. (Customer Sample Comment: 400hr Oil Sample)

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



OIL ANALYSIS REPORT



Submitted By: DARREL HILTZ

Page 2 of 2