


# **OIL ANALYSIS REPORT**

# LACTOSE [1792213] **CY12AG01GB01**

Component

Gearbox

**MOBIL SHC CIBUS 220 (--- QTS)** 





#### Recommendation

Resample at the next service interval to monitor. NOTE: Please provide information regarding reservoir capacity, filter type and micron rating with next sample.

#### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the

### **Fluid Condition**

The condition of the oil is acceptable for the time in service.

Aug <sup>2</sup> 016 Feb <sub>2</sub> 019 Aug <sup>2</sup> 019 Aug <sup>2</sup> 020 Feb <sub>2</sub> 021 Aug <sup>2</sup> 022 Feb <sub>2</sub> 023 Aug <sup>2</sup> 023									
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2			
Sample Number		Client Info		WC0838504	WC0783354	WC0697424			
Sample Date		Client Info		09 Aug 2023	09 Feb 2023	10 Aug 2022			
Machine Age	mths	Client Info		0	0	0			
Oil Age	mths	Client Info		0	0	0			
Oil Changed		Client Info		N/A	N/A	N/A			
Sample Status				NORMAL	NORMAL	ABNORMAL			
WEAR METALS		method	limit/base	current	history1	history2			
Iron	ppm	ASTM D5185m	>200	0	4	3			
Chromium	ppm	ASTM D5185m	>15	0	<1	<1			
Nickel	ppm	ASTM D5185m	>15	0	<1	0			
Titanium	ppm	ASTM D5185m		0	0	0			
Silver	ppm	ASTM D5185m		0	0	<1			
Aluminum	ppm	ASTM D5185m	>25	0	<1	0			
Lead	ppm	ASTM D5185m	>100	0	0	0			
Copper	ppm	ASTM D5185m	>200	0	<1	0			
Tin	ppm	ASTM D5185m	>25	0	0	0			
Antimony	ppm	ASTM D5185m	>5						
Vanadium	ppm	ASTM D5185m		0	<1	0			
Cadmium	ppm	ASTM D5185m		0	0	0			
ADDITIVES		method	limit/base	current	history1	history2			
Boron	ppm	ASTM D5185m		0	1	<1			
Barium	ppm	ASTM D5185m		0	0	0			
Molybdenum	ppm	ASTM D5185m		0	0	0			
Manganese	ppm	ASTM D5185m		<1	<1	<1			
Magnesium	ppm	ASTM D5185m		<1	0	<1			
Calcium	ppm	ASTM D5185m		0	0	1			
Phosphorus	ppm	ASTM D5185m		531	247	271			
Zinc	ppm	ASTM D5185m		0	8	6			
Sulfur	ppm	ASTM D5185m		611	285	329			
CONTAMINANTS		method	limit/base	current	history1	history2			
Silicon	ppm	ASTM D5185m	>50	5	30	29			
Sodium	ppm	ASTM D5185m		<1	0	0			
Potassium	ppm	ASTM D5185m	>20	0	<1	<1			
VISUAL		method	limit/base	current	history1	history2			
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE			
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE			
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE			
Silt	scalar	*Visual	NONE	NONE	NONE	NONE			
Debris	scalar	*Visual	NONE	NONE	LIGHT	NONE			
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE			
Appearance	scalar	*Visual	NORML	NORML	NORML	▲ SOLID			
Odor	scalar	*Visual	NORML	NORML	NORML	NORML			
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG			
- 14/ -									

Free Water


scalar \*Visual

NEG ▲ 1.0

NEG





# **OIL ANALYSIS REPORT**




FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	222	217	198	199
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color				no image	no image	no image
Bottom				no image	no image	no image

#### **GRAPHS**









Certificate L2367

Laboratory Sample No. Lab Number

Test Package : IND 1

: WC0838504 : 05926502 Unique Number : 10606449

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 16 Aug 2023 Diagnosed : 17 Aug 2023

Diagnostician : Wes Davis

**LEPRINO FOODS-GREELEY** 

1302 1ST AVE GREELEY, CO US 80631-5909

Contact: ERIC KLINE

EKLINE@LEPRINOFOODS.COM

To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (970)347-5190