




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**Huntington**  
Machine Id  
**[Huntington] Oil - Starboard Main Engine**  
Component  
**Starboard Main Engine**  
Fluid  
**DIESEL ENGINE OIL SAE 15W40 (165 GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the brand, type, and viscosity of the oil on your next sample.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

method	limit/base	current	history1	history2	
Sample Number	Client Info	<b>WC0769355</b>	WC0769140	WC0769222	
Sample Date	Client Info	<b>08 Aug 2023</b>	08 Jul 2023	13 Jun 2023	
Machine Age	hrs	Client Info	<b>16442</b>	16442	14790
Oil Age	hrs	Client Info	<b>16442</b>	0	14790
Oil Changed	Client Info	<b>N/A</b>	N/A	N/A	
Sample Status		<b>NORMAL</b>	NORMAL	NORMAL	

## CONTAMINATION

method	limit/base	current	history1	history2
Fuel	WC Method >4.0	<b>&lt;1.0</b>	<1.0	<1.0
Glycol	WC Method	<b>NEG</b>	NEG	NEG

## WEAR METALS

method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m >75	<b>6</b>	6	5
Chromium	ppm	ASTM D5185m >8	<b>&lt;1</b>	0	<1
Nickel	ppm	ASTM D5185m >2	<b>0</b>	0	<1
Titanium	ppm	ASTM D5185m >3	<b>0</b>	0	<1
Silver	ppm	ASTM D5185m >2	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m >15	<b>3</b>	2	0
Lead	ppm	ASTM D5185m >18	<b>3</b>	2	3
Copper	ppm	ASTM D5185m >80	<b>10</b>	4	9
Tin	ppm	ASTM D5185m >14	<b>&lt;1</b>	0	<1
Vanadium	ppm	ASTM D5185m	<b>0</b>	<1	0
Cadmium	ppm	ASTM D5185m	<b>0</b>	0	<1

## ADDITIVES

method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m 250	<b>161</b>	177	221
Barium	ppm	ASTM D5185m 10	<b>0</b>	0	5
Molybdenum	ppm	ASTM D5185m 100	<b>95</b>	96	97
Manganese	ppm	ASTM D5185m	<b>&lt;1</b>	<1	<1
Magnesium	ppm	ASTM D5185m 450	<b>748</b>	692	708
Calcium	ppm	ASTM D5185m 3000	<b>1626</b>	1704	1722
Phosphorus	ppm	ASTM D5185m 1150	<b>856</b>	837	887
Zinc	ppm	ASTM D5185m 1350	<b>1058</b>	1067	1097
Sulfur	ppm	ASTM D5185m 4250	<b>3527</b>	3514	3633

## CONTAMINANTS

method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m >20	<b>5</b>	3	8
Sodium	ppm	ASTM D5185m >158	<b>1</b>	1	4
Potassium	ppm	ASTM D5185m >20	<b>0</b>	2	4

## INFRA-RED



method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	<b>0.2</b>	0.2	0.2
Nitration	Abs/cm	*ASTM D7624 >20	<b>9.2</b>	9.3	8.5
Sulfation	Abs/.1mm	*ASTM D7415 >30	<b>21.6</b>	22.9	22.5

## FLUID DEGRADATION

method	limit/base	current	history1	history2	
Oxidation	Abs/.1mm	*ASTM D7414 >25	<b>18.0</b>	18.8	19.0
Base Number (BN)	mg KOH/g	ASTM D2896 8.5	<b>9.21</b>	15.40	9.40







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.1	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	<b>13.2</b>	13.4	13.6

## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : WC0769355 **Received** : 17 Aug 2023  
**Lab Number** : 05927457 **Diagnosed** : 18 Aug 2023  
**Unique Number** : 10607404 **Diagnostician** : Wes Davis  
**Test Package** : IND 2

**MARATHON PETROLEUM CO.**  
 101 12TH ST  
 CATLETTSBURG, KY  
 US 41169  
 Contact: CORY GUMBERT  
 cagumbert@marathonpetroleum.com  
 T: (606)585-3950  
 F: x:

To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)