


OIL ANALYSIS REPORT

HINO [600380369] 36WEA81846

Wind Turbine Gearbox

CASTROL OPTIGEAR SYNTHETIC X 320 (--- LTR)





Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| | ug2012 May2014 0:d2015 Apr2017 0:d2018 Sap2020 Apr2022 | | | | | |
|-----------------|--|--------------|------------|-------------|-------------|-------------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | NX05928215 | NX05700281 | NX05602725 |
| Sample Date | | Client Info | | 10 Apr 2023 | 06 Oct 2022 | 11 Apr 2022 |
| Machine Age | mths | Client Info | | 0 | 0 | 0 |
| Oil Age | mths | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | N/A | N/A | N/A |
| Sample Status | | | | NORMAL | NORMAL | NORMAL |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| PQ | | ASTM D8184 | >80 | 14 | 5 | 14 |
| Iron | ppm | ASTM D5185m | >150 | 2 | 0 | <1 |
| Chromium | ppm | ASTM D5185m | >5 | 0 | 0 | 0 |
| Nickel | ppm | ASTM D5185m | >10 | 1 | 0 | <1 |
| Titanium | ppm | ASTM D5185m | >10 | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185m | | 0 | 0 | <1 |
| Aluminum | ppm | ASTM D5185m | >10 | <1 | 0 | <1 |
| Lead | ppm | ASTM D5185m | >20 | 0 | <1 | <1 |
| Copper | ppm | ASTM D5185m | >50 | 1 | <1 | <1 |
| Tin | ppm | ASTM D5185m | >10 | 0 | 0 | <1 |
| Antimony | ppm | ASTM D5185m | >5 | | | |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | 32 | <1 |
| Barium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | 1150 | 884 | 599 | 530 |
| Manganese | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Magnesium | ppm | ASTM D5185m | | 6 | 5 | 3 |
| Calcium | ppm | ASTM D5185m | 2000 | 1579 | 1089 | 1043 |
| Phosphorus | ppm | ASTM D5185m | 400 | 389 | 272 | 240 |
| Zinc | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Sulfur | ppm | ASTM D5185m | 1850 | 2383 | 1881 | 1458 |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >50 | 11 | 8 | 6 |
| Sodium | ppm | ASTM D5185m | >20 | 8 | 3 | 3 |
| Potassium | ppm | ASTM D5185m | >20 | 1 | 0 | 0 |
| Water | % | ASTM D6304 | >0.05 | 0.027 | 0.021 | 0.033 |
| ppm Water | ppm | ASTM D6304 | >500 | 275.6 | 214.0 | 333.4 |
| FLUID CLEANLIN | ESS | method | limit/base | current | history1 | history2 |
| Particles >4µm | | ASTM D7647 | | 1645 | 3260 | 454 |
| Particles >6µm | | ASTM D7647 | >2500 | 266 | 781 | 98 |
| Particles >14μm | | ASTM D7647 | >320 | 19 | 42 | 10 |
| Particles >21µm | | ASTM D7647 | >80 | 7 | 8 | 3 |
| Particles >38µm | | ASTM D7647 | >20 | 0 | 0 | 0 |
| Particles >71μm | | ASTM D7647 | >4 | 0 | 0 | 0 |
| Oil Cleanliness | | ISO 4406 (c) | >/18/15 | 18/15/11 | 19/17/13 | 16/14/10 |
| | | . / | | | | |



OIL ANALYSIS REPORT



* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: x: F: x: