


# **OIL ANALYSIS REPORT**

# HINO [600380370] 37WEA81866

**Wind Turbine Gearbox** 

**CASTROL OPTIGEAR SYNTHETIC X 320 (--- LTR)** 





### Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		ug2012 Jun2	014 Oct2015 May2017	Oct2018 Apr2020 Nov2021	0ct2022	
SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		NX05928231	NX05700246	NX05602758
Sample Date		Client Info		23 May 2023	25 Oct 2022	01 Jun 2022
Machine Age	mths	Client Info		0	0	0
Oil Age	mths	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	ATTENTION
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184	>80	17	6	20
Iron	ppm	ASTM D5185m	>150	6	4	3
Chromium	ppm	ASTM D5185m	>5	0	0	0
Nickel	ppm	ASTM D5185m	>10	<1	0	0
Titanium	ppm	ASTM D5185m	>10	0	0	0
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m	>10	<1	0	<1
Lead	ppm	ASTM D5185m	>20	0	<1	<1
Copper	ppm	ASTM D5185m	>50	6	12	12
Tin	ppm	ASTM D5185m	>10	0	0	<1
Antimony	ppm	ASTM D5185m	>5			
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	38	<1
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m	1150	693	673	530
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m		5	6	3
Calcium	ppm	ASTM D5185m	2000	1321	1411	1123
	ppm	ASTM D5185m	400	308	318	245
Zinc	ppm	ASTM D5185m	0	<1	0	0
Sulfur	ppm	ASTM D5185m	1850	1899	1926	1447
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	8	9	6
Sodium	ppm	ASTM D5185m	>20	4	5	4
Potassium	ppm	ASTM D5185m	>20	<1	0	0
Water	%	ASTM D6304	>0.05	0.031	0.021	0.039
ppm Water	ppm	ASTM D6304	>500	311.8	217.2	396.7
FLUID CLEANLINE	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		10633	4435	25729
Particles >6µm		ASTM D7647	>2500	1574	489	▲ 3000
Particles >14μm		ASTM D7647	>320	68	21	111
Particles >21µm		ASTM D7647	>80	15	5	17
Particles >38µm		ASTM D7647	>20	0	0	1
Particles >38μm Particles >71μm		ASTM D7647 ASTM D7647		0	0	1



## **OIL ANALYSIS REPORT**



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: x: