




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id
CHEVY 2500 602102 - 2021 CHEVY 2500 4X4 (S/N 1GC5YLE75MF254425)

Component
Gasoline Engine

Fluid
PETRO CANADA DURON ADVANCED 5W30 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		SBP0004667	SBP0004473	SBP0003796
Sample Date	Client Info		16 Aug 2023	08 Jun 2023	17 Mar 2023
Machine Age	hrs	Client Info	2549	2235	1933
Oil Age	hrs	Client Info	314	302	353
Oil Changed	Client Info		Changed	Changed	Not Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>4.0	<1.0	<1.0	<1.0
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >150	7	9	9
Chromium	ppm	ASTM D5185m >20	<1	<1	<1
Nickel	ppm	ASTM D5185m >5	<1	<1	<1
Titanium	ppm	ASTM D5185m	<1	<1	<1
Silver	ppm	ASTM D5185m >2	0	0	0
Aluminum	ppm	ASTM D5185m >40	2	1	3
Lead	ppm	ASTM D5185m >50	<1	0	0
Copper	ppm	ASTM D5185m >155	1	1	1
Tin	ppm	ASTM D5185m >10	2	2	<1
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	23	37	54
Barium	ppm	ASTM D5185m 0	0	2	0
Molybdenum	ppm	ASTM D5185m 43	72	96	69
Manganese	ppm	ASTM D5185m 0	<1	<1	<1
Magnesium	ppm	ASTM D5185m 920	486	501	478
Calcium	ppm	ASTM D5185m 1330	1215	1246	1219
Phosphorus	ppm	ASTM D5185m 790	646	701	645
Zinc	ppm	ASTM D5185m 880	791	843	780
Sulfur	ppm	ASTM D5185m 2200	2859	3128	2652

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >30	10	11	9
Sodium	ppm	ASTM D5185m >400	1	1	2
Potassium	ppm	ASTM D5185m >20	<1	1	<1

INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	0	0.1	0.1
Nitration	Abs/cm	*ASTM D7624 >20	9.7	10.4	10.5
Sulfation	Abs/.1mm	*ASTM D7415 >30	22.4	22.4	23.0

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	16.6	17.5	15.9
Base Number (BN)	mg KOH/g	ASTM D2896 12.0	3.5	5.0	4.2







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	10.0	9.9	10.0	10.2

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : SBP0004667 **Received** : 21 Aug 2023
Lab Number : **05929353** **Diagnosed** : 22 Aug 2023
Unique Number : 10609300 **Diagnostician** : Angela Borella
Test Package : FLEET

Constructors Inc. - 603659
 1815 Y Street
 Lincoln, NE
 US 68508
 Contact: Jack Linhart
 jackl@constructorslincoln.com
 T: (402)434-2157
 F:

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)