

# **OIL ANALYSIS REPORT**

Sample Rating Trend

NORMAL



# **DRYERS C-603** Component

Gearbox

MOBIL SHC 630 (8 QTS)

D	IA	Gľ	VО	SI	S	

## Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

## Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

Janitoso Martoso Sapitoso Apriloso Octoso Martosos Sapitoso Federos Augústos								
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2		
Sample Number		Client Info		WC0849092	WC0788655	WC0739606		
Sample Date		Client Info		17 Aug 2023	09 Feb 2023	14 Sep 2022		
Machine Age	yrs	Client Info		3	2	2		
Oil Age	yrs	Client Info		2	1	1		
Oil Changed		Client Info		N/A	Not Changd	Not Changd		
Sample Status				NORMAL	MARGINAL	ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2		
Iron	ppm	ASTM D5185m	>200	0	14	15		
Chromium	ppm	ASTM D5185m	>15	0	0	0		
Nickel	ppm	ASTM D5185m	>15	<1	0	0		
Titanium	ppm	ASTM D5185m		0	0	0		
Silver	ppm	ASTM D5185m		0	0	<1		
Aluminum	ppm	ASTM D5185m	>25	0	0	0		
Lead	ppm	ASTM D5185m	>100	<1	0	0		
Copper	ppm	ASTM D5185m	>200	0	0	0		
Tin	ppm	ASTM D5185m	>25	0	0	<1		
Vanadium	ppm	ASTM D5185m		0	0	0		
Cadmium	ppm	ASTM D5185m		0	0	0		
ADDITIVES		method	limit/base	current	history1	history2		
Boron	ppm	ASTM D5185m		0	0	0		
Barium	ppm	ASTM D5185m		0	0	0		
Molybdenum	ppm	ASTM D5185m		0	0	0		
Manganese	ppm	ASTM D5185m		0	<1	<1		
Magnesium	ppm	ASTM D5185m		<1	0	0		
Calcium	ppm	ASTM D5185m		0	<1	0		
Phosphorus	ppm	ASTM D5185m		409	416	455		
Zinc	ppm	ASTM D5185m		0	1	4		
Sulfur	ppm	ASTM D5185m		35	18	0		
CONTAMINANTS		method	limit/base	current	history1	history2		
Silicon	ppm	ASTM D5185m	>50	6	<u> </u>	<u> </u>		
Sodium	ppm	ASTM D5185m		0	0	0		
Potassium	ppm	ASTM D5185m	>20	<1	<1	0		
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2		
Particles >4µm		ASTM D7647	>20000	1476				
Particles >6µm		ASTM D7647	>5000	376				
Particles >14µm		ASTM D7647	>640	32				
Particles >21µm		ASTM D7647	>160	12				
Particles >38μm		ASTM D7647	>40	1				
Particles >71μm		ASTM D7647	>10	0				
Oil Cleanliness		ISO 4406 (c)	>21/19/16	18/16/12				
FLUID DEGRADA	TION	method	limit/base	current	history1	history2		
Acid Number (AN)	mg KOH/g	ASTM D8045		0.35	0.35	0.42		



## OIL ANALYSIS REPORT







Certificate L2367

Laboratory Sample No. **Unique Number** 

Lab Number

Test Package : IND 2 ( Additional Tests: PrtCount )

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 05929833

: WC0849092 : 10615104

Received Diagnosed Diagnostician

: 21 Aug 2023 : 24 Aug 2023 : Angela Borella

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

**POET BIOREFINING - Groton** 

40425 133RD STREET GROTON, SD US 57445-6400

Contact: GAVIN KRUEGER Gavin.Krueger@POET.COM T: 6(05)846-6863

F: (605)397-2754