

OIL ANALYSIS REPORT

Sample Rating Trend



KAESER BSD 60 6948689 (S/N 1553) Component

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


		Oct201	9 Oct2020	Mar2022 Au	g2023	
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA006739	KCP44169	KCP30554
Sample Date		Client Info		14 Aug 2023	18 Mar 2022	03 Oct 2020
Machine Age	hrs	Client Info		22800	15415	7558
Oil Age	hrs	Client Info		11713	7800	7558
Oil Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	ABNORMAL	ATTENTION
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	<1	<1
Aluminum	ppm	ASTM D5185m		0	<1	0
Lead		ASTM D5185m	>10	0	0	0
	ppm			6	6	
Copper	ppm	ASTM D5185m		-		6
Tin	ppm	ASTM D5185m	>10	0	<1	0
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	<1	10
Barium	ppm	ASTM D5185m	90	0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	90	0	0	<1
Calcium	ppm	ASTM D5185m	2	0	0	0
Phosphorus	ppm	ASTM D5185m		0	<1	1
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		15340	12994	13911
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	0	<1
Sodium	ppm	ASTM D5185m		1	<1	<1
Potassium	ppm	ASTM D5185m	>20	<1	0	0
Water	%	ASTM D6304	>0.05	0.007	0.009	0.006
ppm Water	ppm	ASTM D6304	>500	71.3	91.0	66.8
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		1122	12872	2501
Particles >6μm		ASTM D7647	>1300	395	▲ 5145	737
Particles >14µm		ASTM D7647	>80	63	<u> </u>	9 4
Particles >21µm		ASTM D7647		24	<u>▲</u> 50	▲ 30
Particles >38µm		ASTM D7647	>4	3	4	1
Particles >71µm		ASTM D7647		0	0	0
Oil Cleanliness		ISO 4406 (c)	>3	0 17/16/13	20/15	17/14
FLUID DEGRADA	TION	method	limit/base		history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.42	0.38	0.331
:12:05) Rev: 1			С	ontact/Location:	Service Manac	per - PRICARG


Report Id: PRICARGA [WUSCAR] 05930385 (Generated: 08/23/2023 15:12:05) Rev: 1


Contact/Location: Service Manager - PRICARGA



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPER	ΓIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	44.6	44.3	43.9
SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Color						
Bottom						11255

