

OIL ANALYSIS REPORT

Ewing Hauling **AUTOCAR 6714**

Component **Diesel Engine**

GIBRALTAR 15W/40 SUPER S-3 LX (11)

Sample Rating Trend



Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

				lug2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0830858		
Sample Date		Client Info		10 Aug 2023		
Machine Age	hrs	Client Info		11542		
Oil Age	hrs	Client Info		150		
Oil Changed		Client Info		Filtered		
Sample Status				NORMAL		
CONTAMINATION	N	method	limit/base	current	history1	history2
Fuel		WC Method	>5	<1.0		
Glycol		WC Method		NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	8		
Chromium	ppm	ASTM D5185m	>20	<1		
Nickel	ppm	ASTM D5185m	>4	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m	>3	0		
Aluminum	ppm	ASTM D5185m	>20	<1		
Lead	ppm	ASTM D5185m	>40	<1		
Copper	ppm	ASTM D5185m		10		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m	7.0	<1		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES	ppm	method	limit/base	current	history1	history2
			limit/base			
ADDITIVES	ppm	method ASTM D5185m	limit/base	current	history1	
ADDITIVES Boron Barium	ppm ppm	method	limit/base	current	history1	history2
ADDITIVES Boron Barium Molybdenum	ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m		current 11 0 67	history1	history2
ADDITIVES Boron Barium Molybdenum Manganese	ppm ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m		current 11 0 67 <1	history1 	history2
ADDITIVES Boron Barium Molybdenum	ppm ppm ppm ppm	method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	66	current 11 0 67 <1 833	history1	history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm	method ASTM D5185m	66	current 11 0 67 <1 833 1330	history1	history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm ppm ppm	method ASTM D5185m	66 1000 1050 1150	current 11 0 67 <1 833	history1	history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm	method ASTM D5185m	66 1000 1050	current 11 0 67 <1 833 1330 1056	history1	history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m	66 1000 1050 1150	current 11 0 67 <1 833 1330 1056 1263	history1	history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m	1000 1050 1150 1270	current 11 0 67 <1 833 1330 1056 1263 3760	history1	history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m	66 1000 1050 1150 1270	current 11 0 67 <1 833 1330 1056 1263 3760 current	history1 history1	history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon	ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m	66 1000 1050 1150 1270	current 11 0 67 <1 833 1330 1056 1263 3760 current	history1 history1	history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m	66 1000 1050 1150 1270 limit/base >25	current 11 0 67 <1 833 1330 1056 1263 3760 current 4	history1 history1	history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m	66 1000 1050 1150 1270 limit/base >25 >20	current 11 0 67 <1 833 1330 1056 1263 3760 current 4 4	history1 history1	history2 history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m	66 1000 1050 1150 1270 limit/base >25 >20 limit/base	current 11 0 67 <1 833 1330 1056 1263 3760 current 4 0 current	history1 history1 history1	history2 history2 history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m method ASTM D5185m	66 1000 1050 1150 1270 limit/base >25 >20 limit/base >3	current 11 0 67 <1 833 1330 1056 1263 3760 current 4 4 0 current	history1 history1 history1	history2 history2 history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m method ASTM D5185m	66 1000 1050 1150 1270 limit/base >25 >20 limit/base >3 >20	current 11 0 67 <1 833 1330 1056 1263 3760 current 4 4 0 current 0.3 8.3	history1 history1 history1	history2 history2 history2
ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	method ASTM D5185m method ASTM D5185m ASTM D5185m *ASTM D5185m ASTM D5185m *ASTM D5185m ASTM D5185m ASTM D5185m *ASTM D5185m ASTM D5185m *ASTM D5185m *ASTM D7844 *ASTM D7624 *ASTM D76185m *ASTM D76185m	66 1000 1050 1150 1270 limit/base >25 >20 limit/base >3 >20 >30	current 11 0 67 <1 833 1330 1056 1263 3760 current 4 4 0 current 0.3 8.3 19.3	history1 history1 history1	history2 history2 history2 history2




OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPERT	TIES	method	limit/base		history1	history2

Visc @ 100°C cSt	ASTM D445	15.5	14.1	
------------------	-----------	------	------	--



10 T		
6		
Edd 4		
2		
0		33
Aug10/23		Aug10/23
Viscosity	v @ 100°C	









Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10616727

: WC0830858 : 05931456 Test Package : FLEET

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received

Diagnosed

: 22 Aug 2023 : 24 Aug 2023

Diagnostician : Don Baldridge

EWING TOWNSHIP, NJ US 08638 Contact: Carlos Evans

CEvans@interstatewaste.com T:

INTERSTATE WASTE-EWING

432 STOKES AVENUE

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

F: