


OIL ANALYSIS REPORT

Sample Rating Trend







MB10078L

Component

Hydraulic System

PHILLIPS 66 Powerflow NZ AW46 (--- QTS)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the

Fluid Condition

The condition of the oil is acceptable for the time in service.

						<u>'</u>
			Jan 2022	Aug 2023		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0848741	WC0653895	
Sample Date		Client Info		11 Aug 2023	27 Jan 2022	
Machine Age	hrs	Client Info		0	0	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		N/A	N/A	
Sample Status				NORMAL	NORMAL	
WEAR METALS		method	limit/base	current	history1	history2
ron	ppm	ASTM D5185m	>20	4	3	
Chromium	ppm	ASTM D5185m	>20	2	<1	
Nickel	ppm	ASTM D5185m	>20	0	0	
Titanium	ppm	ASTM D5185m		0	0	
Silver	ppm	ASTM D5185m		0	0	
Aluminum	ppm	ASTM D5185m	>20	0	<1	
ead	ppm	ASTM D5185m	>20	<1	0	
Copper	ppm	ASTM D5185m	>20	3	8	
-in	ppm	ASTM D5185m	>20	0	<1	
/anadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	<1	
Barium	ppm	ASTM D5185m		0	0	
/lolybdenum	ppm	ASTM D5185m		<1	<1	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m		4	3	
Calcium	ppm	ASTM D5185m		55	56	
Phosphorus	ppm	ASTM D5185m		331	285	
Zinc	ppm	ASTM D5185m		408	371	
Sulfur	ppm	ASTM D5185m		1026	872	
CONTAMINANTS	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	<1	
Sodium	ppm	ASTM D5185m		0	0	
Potassium	ppm	ASTM D5185m	>20	1	0	
VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	
ellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	
Free Water	scalar	*Visual		NEG	NEG	
FLUID PROPER	TIES	method	limit/base	current	history1	history2
	_					


Visc @ 40°C

cSt

ASTM D445 46





OIL ANALYSIS REPORT






GRAPHS











Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10617741 Test Package : IND 1

: WC0848741 : 05932470

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 23 Aug 2023 Diagnosed : 25 Aug 2023 Diagnostician : Jonathan Hester

SUMIRIKO TENNESSEE INC 150 HESTER LN TAZEWELL, TN US 37879 Contact: JEREMY COLLINS

jcollins@us.sumiriko.com T: (423)626-8805 F: (423)626-2065

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)