


OIL ANALYSIS REPORT

Sample Rating Trend







MB9995L

Component

Hydraulic System

PHILLIPS 66 Powerflow NZ AW46 (--- QTS)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The condition of the oil is acceptable for the time in service.

			Mar ² 022	Aug 2023		
SAMPLE INFOR	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info	mma sass	WC0848730	WC0653890	
Sample Date		Client Info		11 Aug 2023	14 Mar 2022	
Machine Age	hrs	Client Info		0	0	
Dil Age	hrs	Client Info		0	0	
Oil Changed	1113	Client Info		N/A	N/A	
Sample Status		Ollerit IIIIO		NORMAL	NORMAL	
WEAR METALS		method	limit/base		history1	history2
ron	ppm	ASTM D5185m	>20	4	2	
Chromium	ppm	ASTM D5185m	>20	1	0	
Nickel 	ppm	ASTM D5185m	>20	0	<1	
- itanium	ppm	ASTM D5185m		0	<1	
Silver	ppm	ASTM D5185m		0	<1	
Aluminum	ppm	ASTM D5185m	>20	0	<1	
ead	ppm	ASTM D5185m	>20	<1	0	
Copper	ppm	ASTM D5185m	>20	6	8	
īin	ppm	ASTM D5185m	>20	0	<1	
/anadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	<1	
Barium	ppm	ASTM D5185m		0	1	
Nolybdenum	ppm	ASTM D5185m		1	0	
<i>M</i> anganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m		5	0	
Calcium	ppm	ASTM D5185m		65	45	
Phosphorus	ppm	ASTM D5185m		335	253	
Zinc	ppm	ASTM D5185m		420	338	
Sulfur	ppm	ASTM D5185m		786	787	
CONTAMINANT	S	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	<1	<1	
Sodium	ppm	ASTM D5185m		0	0	
Potassium	ppm	ASTM D5185m	>20	1	0	
VISUAL		method	limit/base	current	history1	history:
Vhite Metal	scalar	*Visual	NONE	NONE	NONE	
ellow Metal	scalar	*Visual	NONE	NONE	NONE	
Precipitate	scalar	*Visual	NONE	NONE	NONE	
Silt	scalar	*Visual	NONE	NONE	NONE	
Debris	scalar	*Visual	NONE	NONE	NONE	
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	
Appearance	scalar	*Visual	NORML	NORML	NORML	
Odor	scalar	*Visual	NORML	NORML	NORML	
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	
ree Water	scalar	*Visual		NEG	NEG	
FLUID PROPER		method	limit/base	current	history1	history2
/isc @ 40°C	cSt	ASTM D445	46	45.3	46.4	
7150 W 40 O	USI	A3 1 W D445	40	45.3	40.4	





OIL ANALYSIS REPORT






GRAPHS











Certificate L2367

Laboratory Sample No. Lab Number Unique Number : 10617777 Test Package : IND 1

: WC0848730 : 05932506

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 23 Aug 2023 Diagnosed : 25 Aug 2023 Diagnostician : Jonathan Hester

jcollins@us.sumiriko.com T: (423)626-8805

SUMIRIKO TENNESSEE INC

Contact: JEREMY COLLINS

150 HESTER LN

TAZEWELL, TN

F: (423)626-2065

US 37879

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: DTRTAZ [WUSCAR] 05932506 (Generated: 08/25/2023 12:34:25) Rev: 1

Contact/Location: JEREMY COLLINS - DTRTAZ