

# **OIL ANALYSIS REPORT**

## Sample Rating Trend

# NORMAL



# Thermoforming Machine Id Line 10 B Extruder (S/N X8192)

Componen

**Bevel Helical Gearbox** 

**SUMMIT UNIPAR FG-150 (8 GAL)** 

# Fluid

## Recommendation

Resample at the next service interval to monitor. ( Customer Sample Comment: Beanjamin castillo )

### Wear

All component wear rates are normal.

## Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

	oumpro maning menu					
Aug2022	Aug2022 Oct2022	Nov2022 Jan2023	Feb 2023 Feb 2023 Apr 202	3 Aug2023		
method	limit/	base	current	h		
		Augžozz Augžozz Oczosz	Aughozz Aughozz Occiosz Novicozz Jandozz	Aug 2022 Aug 1022 Oct 2022 Nov 2022 Sun 2022 Feb 2023 Feb 2023 Apr 2020 Aug 1022 Aug		

Sample Number		Client Info		TO50001558	TO50001596	TO50001402
Sample Date		Client Info		18 Aug 2023	05 Apr 2023	27 Feb 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	ATTENTION	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184		12	12	12
Iron	ppm	ASTM D5185m	>150	0	2	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>10	0	<1	0
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	0	0	0
Lead	ppm	ASTM D5185m	>100	0	0	0
Copper	ppm	ASTM D5185m	>50	<1	<1	0
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		2	1	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		<1	0	5
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m		655	655	564
Zinc	ppm	ASTM D5185m		2	<1	4
Sulfur	ppm	ASTM D5185m		331	662	427
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	21	29	62
Sodium	ppm	ASTM D5185m	>00	0	0	0
Potassium	ppm	ASTM D5185m	>20	1	0	0
Water	%	ASTM D6304	>0.1	0.005	0.003	
ppm Water	ppm	ASTM D6304	>1000	51.8	28.3	
FLUID CLEANLIN		method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>1300	977	<u>△</u> 2059	
Particles >4μm		ASTM D7647		306	▲ 539	
Particles >6µm		ASTM D7647	>80	37	40	
Particles >14μm		ASTM D7647		13	12	
Particles >21µm		ASTM D7647	>4	2	0	
Particles >36µm		ASTM D7647 ASTM D7647		0	0	
Oil Cleanliness		ISO 4406 (c)	>3 >17/15/13	17/15/12		
				17/13/12		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

0.69

mg KOH/g ASTM D8045

Acid Number (AN)



# **OIL ANALYSIS REPORT**

